WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No. 20,092	
1 LOCATION OF WATER WELL:	Fraction	Section Number Township No. Range Num	nber
County: FINNEY	1/4 NW 1/4 NW 1/4 SE 1/4		JE ZW
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here		Global Positioning System (GPS) information:	
HOLCOMB-4 M S, 1 M W, 6 M S TO PARALLEL RD, 3 M E,		Latitude:	
1 M N, 2,142 FT. NORTH & 2,306 FT WEST		Elevation:	
2 WATER WELL OWNER: REEVE CATTLE CO., INC.		Datum: WGS 84, NAD 83, NAD 27 Collection Method:	
RR#, Street Address, Box #: P. O. BOX 1036		GPS unit (Make/Model:)	
City, State, ZIP Code : GARDE	N CITY, KANSAS 67846	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Lar Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >	
3 LOCATE WELL			
WITH AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered (1) ft (2) ft (3)			
SECTION BOX: Depth(s) Groundwater Encountered (1)			
Pump test data: Well water wasft, after hours pumpinggpm			
EST. YIELDgpm. Well water wasft. afterhours pumpinggpm			
W Bore Hole Diameter .30 in. to .430 ft., and in. to ft. WELL WATER TO BE USED AS: Public water supply Geothermal Injection well			
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Domestic Feedlot Oil field water supply Dewatering Other (Specify below)			
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes V No If yes, mo/day/yr sample was submitted			
S If yes, mo/day/yr sample was submitted			
5 TYPE OF CASING USED: Steel PVC Other			
CASING JOINTS: Glued Clamped Welded Threaded			
Casing diameter16 in. to			
Casing height above land surface	in., Weight 42,05	lbs./ft., Wall thickness or gauge No250	• • • • • • • • • • • • • • • • • • • •
TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify)			
Brass Galvanized Steel None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:			
☐ Continuous slot			
SCREEN-PERFORATED INTERVALS: From			
From ft. to ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 20 ft. to 225 ft., From 285 ft. to 430 ft. From ft. to ft., From ft. to ft.			
6 GROUT MATERIAL: ☐ Neat cement			
Grout Intervals: From			
What is the nearest source of possible conta	mination: es Pit privy Divestock p	ens	low
☐ Sewer lines ☐ Cesspool	Sewage lagoon Fuel storage	Abandoned water well	.0W)
	it Feedyard Fertilizer st		
Direction from well		from well TO LITHO. LOG (cont.) or PLUGGING INT	
		Elitio. Log (com.,) GIT Bodding invi	DICYTES
OFF ATTACHED LOC			
SEE ATTACHED LOG			
			<u> </u>
			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged			
under my jurisdiction and was completed on (mo/day/year) .6-14-13 and this record is true to the best of my knowledge and belief.			
Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/year) 6-20-13			
under the business name ofMINTER-WILSON DRILLING.CO., INC. by (signature)			
(white, blue, pink) to Kansas Depar tment of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 666 12-1367.			
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at http://www.kdheks.gov/waterwell/index.html.			
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy			

The Professionals MINTER-WILSON DRILLING CO.

Irrigation and Domestic **Water Systems** Complete Installation and Repairing

INCORPORATED

Phone 620-276-8269 GARDEN CITY, KANSAS 67846 P.O. Box A .

NAME

REEVE CATTLE COMPANY - CIRCLE # 47

COUNTY

FINNEY

DATE

3-26-13

LOCATION:

SE 1/4 29-25-33 - PARALLEL & ANNE SHEAR ROAD - 2 MILES NORTH,

1/2 MILE EAST, 3/4 OF A MILE SOUTH &

1/4 OF A MILE EAST

- NORTHWEST EDGE OF FIELD-2 TRACKS IN

STATIC WATER LEVEL -

TEST#1

0' TO 1' - TOP SOIL

1' TO 31' - BROWN SANDY CLAY

31' TO 56' - BROWN CLAY

56' TO 205' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

205' TO 228' - BROWN & BLUE CLAY

228' TO 248' - BROWN CLAY - SMALL GRAVEL STREAKS

248' TO 292' - BROWN CLAY

292' TO 310' - FINE TO MEDIUM SAND & GRAVEL

310' TO 334' - BROWN SANDY CLAY

334' TO 344' - FINE TO MEDIUM SAND & GRAVEL

344' TO 368' - BROWN CLAY

368' TO 408' - FINE TO MEDIUM SAND & GRAVEL - 10% CLAY

408' TO 415' - BROWN SANDY CLAY

415' TO 420' - FINE TO MEDIUM FINE SAND

420' TO 430' - BROWN SANDY CLAY

430' TO 468' - BROWN CLAY

468' TO 481' - BROWN YELLOW CLAY - TRACES OF SHALE - HARD

481' TO 485' - SHALE - HARD