VATEI	R WELL I	RECORD	Form WW	C-5	Division of Wate	r Resources; App. No.	20897
1. LOC	ATION OF	WATER WELL:	Fraction		Section Number	Township Number	Range Number
	ty:		NE 1/4 NE 1/4		10 Global Positioning	T 25 S	R 34 EW
Distance and direction from nearest town or city street address of well if located within city? Holcomb Main St. & Hwy. 50-5 M. South , Latitude:							
1 M. West, 2 M. South, 1 M. West, 2200' N. 3000' W. Longitude:							
DD# G: All D. # micron Accor Inc					Elevation:		
City State 7IP Code . 1100 West 116th Ave.					Datum:		
		westminster	r, CO 80234		Data Collection 1	Method:	
	ATE WELI	28 4 DEPTH OF COM	PLEIED WELL	······ 7.+ .	? π.		
WITH AN "X" IN Depth(s) Groundwater Encountered (1)							
SECTION BOX: WELL'S STATIC WATER LEVEL							
Pump test data: Well water wasft. after							
1 '		WELL WATER TO D					
w NV	V NE	E 1 Domestic 3 Fee	dlot 6 Oil fi	eld water s	upply 9 Dew	vatering 12 Of	ther (Specify below)
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well							
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs							
Sample was submitted							
	S						
5 TYPE	E OF CASIN	NG USED: 5 Wrought	Iron 8 C	oncrete tile	CASIN	G JOINTS: Glued	Clamped
		RMP (SR) 6 Asbestos					XX
ZPVC 4 ABS 7 Fiberglass Threaded							
Blank casing diameter16 in. to280 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface12 in., Weight42.05lbs./ft. Wall thickness or guage No250							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify)							
2 Brass 4 Galvanized Steal 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:							
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)							
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)							
SCREEN-PERFORATED INTERVALS: From							
From							
	Old I LE I					ft. to .	
6 CDO	IIT MATEL	DIAL 1 Neet coment 6	Comont amoust 2	Dontonito	4 Othor	. 1/4	110
Grout In	tervals:	RIAL: 1 Neat cement 2 From ft. to	50 ft. From	205	ft. to 265 f	t From	ft. to ft.
		ource of possible contaminate				.,	200 00 1111111120
	Septic tank	4 Lateral lines				secticide Storage	16 Other (specify
	Sewer lines			11 Fuel s	0	bandoned water well	below)
	Watertight so	ewer lines 6 Seepage pit			izer Storage 15 O ny feet?	il well/gas well	'N/A'
FROM	TO	LITHOLOGIC		FRON		PLUGGING INT	ERVALS
		***					WW
		See attached log					
		see accached log					
							*410
			7.4			1160	

7 CONT	TRACTOD'	S OR LANDOWNED'S C	ERTIFICATION	This water	r well was (1) const	ructed (2) reconstruc	ted or (3) plugged
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) .5-22-08 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No 208 This Water Well Record was completed on (mg/day/year)5-23-08							
		ame of Minter-Wilson					
		typewriter or ball point pen. <u>PLE</u> , epartment of Health and Environment					
785-296-5	5522. Send	one to WATER WELL OWN raterwell/index.html.					
nup.//ww\	w.kuncks.gov/W	aterwen/muex.num.					

MINTER-WILSON DRILLING CO. Water Systems Complete Installation

Irrigation and Domestic and Repairing

INCORPORATED

Phone 276-8269

P.O. Box A

GARDEN CITY, KANSAS 67846

NAME

TRI-STATE GENERATION

COUNTY

FINNEY

DATE

3-18-08

LOCATION:

SW 1/4 10-25-34 - SOUTH ON HOLCOMB LANE TO 2ND CURVE,

1-1/2 MILES SOUTH, 1-3/4 MILES WEST &

- BACK NORTHEAST ON CIRCLE

STATIC WATER LEVEL - APPROX. 225 FT.

TEST #1

2' - TOP SOIL O' TO

2' TO 17' - FINE SAND

17' TO 30' - FINE TO MEDIUM SAND & GRAVEL 30' TO 44' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

44' TO 57' - BROWN CLAY

57' TO 70' - MEDIUM TO COARSE GRAVEL

70' TO 87' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

87' TO 144' - BROWN CLAY

144' TO 189' - BROWN CLAY WITH GRAVEL STREAKS

189' TO 198' - FINE TO MEDIUM SAND & GRAVEL

198' TO 204' - BROWN CLAY

204' TO 212' - BLUE CLAY 212' TO 216' - FINE TO MEDIUM SAND & GRAVEL

216' TO 249' - BROWN SANDY CLAY

249' TO 255' - FINE TO MEDIUM SAND & GRAVEL

255' TO 267' - BROWN SANDY CLAY

267' TO 283' - FINE TO MEDIUM SAND & GRAVEL

283' TO 297' - FINE TO MEDIUM SAND & GRAVEL WITH CLAY STREAKS 297' TO 309' - BROWN CLAY

309' TO 343' - BROWN SANDY CLAY

343' TO 352' - FINE TO MEDIUM SAND

352' TO 375' - FINE TO MEDIUM SAND & GRAVEL - 10% CLAY

375' TO 396' - BROWN CLAY

396' TO 401' - FINE TO MEDIUM SAND & GRAVEL - SOME BROWN ROCK 401' TO 424' - BROWN CLAY

424' TO 436' - BROWN & YELLOW CLAY

436' TO 438' - YELLOW CLAY

438' TO 455' - SHALE - HARD PULL DOWN