		RECORD	Form WWC	C -5	Division of V	Water Resources; App. No	29,943
1 LOC	CATION Onty: Fi	F WATER WELL: nney	Fraction NE 1/4 SW 1/4	SW 1/4	Section Numb	er Township Number T 25 S	Range Number
Distance and direction from nearest town or city street address of well if Global Positioning Systems (decimal degrees, min. of 4							
located within city? From Bridge south of Holcomb					Latitude:		
8 mai	les sou	th, 1,301 ft. north	& 4,124 ft. we	st	Longitude:		
			d Electric Coo		Elevation:		
RR#	, St. Addre			•			
City	, State, ZIP		ty, KS 67871			on Mathadi	
3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL							
LOCATION TO COMPLETED WELL							
WITH AN "X" IN Depth(s) Groundwater Encountered (1)							
SECTION BOX: WELL'S STATIC WATER LEVEL							
gpin							
Est. Yieldgpm: Well water wasft. afterhours pumpinggpm WELL WATER TO BE USED AS: Public water supply 8 Air conditioning 11 Injection well							
-1 -1 -1 -1 -1 -1 -1 -1							
W E 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well							
SW SE W							
Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yrs Sample was submitted							
	-	Sample was submitted	l	wate	er well disintect	ed? Yes No	
	S						
5 TYP	E OF CAS	ING USED: 5 Wrought 3 RMP (SR) 6 Asbestos	Iron 8 Cor	crete tile	CAS	SING JOINTS: Glued.	Clamped
	Steel	3 RMP (SR) 6 Asbestos	-Cement 9 Oth	er (specify	below)	Welded	X
2	PVC	4 ABS 7 Fiberglas	<u>ş</u>			Thread	ed
Blank ca	asing diame	ter 16 in. to see be	LOW ft., Diameter		in. to	. ft., Diameter	in. toft.
2 PVC 4 ABS 7 Fiberglass Threaded Blank casing diameter 16 in. to see below ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 24 in., Weight 62.58 lbs./ft. Wall thickness or guage No. 375							
1 YPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify)							
2 Brass 4 Galvanized Steal 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)							
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)							
SCREEN-PERFORATED INTERVALS: From							
From. 390 ft. to 401 ft., From ft. to ft.							
GRAVEL PACK INTERVALS: From							
From ft. to ft., From ft. to ft.							
(CDO	TIT BAATT	DIAL IN A	6		4.04		
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 25 ft., From 25 ft. to 40 ft., From 210 ft. to 230 ft.							
Grout intervals: From v ft. to 25 ft., From 25 ft. to 40 ft., From 210 ft. to 250 ft.							
What is the nearest source of possible contamination:							
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify							
1	Sewer lines	•	8 Sewage lagoon	11 Fuel st		Abandoned water wel	l below)
I .	_	sewer lines 6 Seepage pit	9 Feedyard Northeast			5 Oil well/gas well 290	•••••
	n from wel		,	How man			TEDIA I C
FROM	ТО	LITHOLOGIC	100	FROM	TO	PLUGGING IN	TERVALS
0'	2481	Plain Casing					
2481	318'	Stainless Steel Scr	een /				
318'	352 '	Plain Casing					
352	381'	Stainless Steel Scr	een			D	
381	390'	Plain Casing				See attached Id	уg
390'	401'	Stainless Steel Scr	een				
401'	407'	Plain Casing					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged							
under my jurisdiction and was completed on (mo/day/year)8-15-08 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No 208 This Water Well Record was completed on (mo/day/year) 9-4-08							
		name of Minter-Wilson					
INSTRUC	CTIONS: Us	e typewriter or ball point pen. PLEA	ISE PRESS FIRMLY and	PRINT clear	ly. Please fill in b	lanks, underline or circle the	correct answers. Send top
three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone							
785-296-5		one to WATER WELL OWN waterwell/index.html.	IER and retain one	or your re	ecords. Fee of	\$5.00 for each construc	ted well. Visit us at
11111111111111111111111111111111111111	v.kuncks.gov/	water well/illuex.litill.					

The Professionals

MINTER-WILSON DRILLING CO. Water Systems Complete Installation

Irrigation
and Domestic
Water Systems
Complete Installation
and Repairing

INCORPORATED

Phone 276-8269 • P.O. Box A • GARDEN CITY, KANSAS 67846

Wheatland Electric Finney County 11-15-07

Location: SW\frac{1}{2} 24-25-34 - South on Holcomb Lane - 8-3/4 miles & \frac{1}{2} mile east to well - 290 ft. southwest of Existing Well

#13 TH - 12-07W

Static Water Level - 222 Ft.

0' to l' - Top soil 1' to 31' - Fine sand - loose 31' to 39' - Fine sand 39' to 54' - Fine to medium sand & gravel- 15% clay 54' to 104' - Fine to medium sand & gravel 104' to 108' - Brown clay 108' to 118' - Fine to medium sand & gravel - 10% clay 118' to 121' - Medium to coarse gravel 121' to 145' - Fine to medium sand & gravel 145' to 161' - Fine to medium sand & gravel - 10% clay 161' to 164' - Medium to coarse gravel 164' to 200' - Fine to medium sand & gravel - 15% clay 200' to 210' - Fine to medium sand & gravel 210' to 225' - Brown clay 225' to 248' - Blue clay 248' to 264' - Fine to medium sand & gravel 264' to 313' - Fine to medium sand & gravel - blue clay streaks 313' to 352' - Brown sticky clay 352' to 376' - Fine to medium sand & gravel - 15% clay 376' to 390' - Blue and brown clay 390' to 401! - Fine to medium sand & gravel 401' to 457' - Brown sticky clay 457' to 467' - Yellow clay 467' to 470' - Shale