WAIER WELL RE	COKD	Form W	W C-5	Div	ision of wate	r Resources App. N	0.		
1 LOCATION OF WA County: FINNEY	TER WELL:	Fraction	1/4 NF 1/4	Section	n Number 9	Township No. T 25 S	Range Number R 34 □E 🗹W		
	of Well Location:		NE 1/4 NE 1/4 NE 1/4			Global Positioning System (GPS) information:			
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here					Latitude: (in decimal degrees)				
					Longitude: (in decimal degrees)				
HOLCOMB-HWY 50-5 M. SOUTH, 1 M. WEST, 2 M. SOUTH,					Elevation: (in decimal degrees)				
2 M. WEST, 4,680 FT. NORTH & 233 FT WEST					Datum: ☐ WGS 84, ☐ NAD 83, ☐ NAD 27				
2 WATER WELL OWNER: TRI-STATE GENERATION & TRANS					Collection Method:				
RR#, Street Address,		GPS unit (Make/Model:)							
City, State, ZIP Code	′. 116 AVE. ⁄IINSTER, CO. 80234	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey							
•	VVLOTIV	11140 1 LTX, OO. 0020-	•	Est. Ac	curacy: \square <	3 m, 🔲 3-5 m, 🗀] 5-15 m,		
WITH AN "X" IN SECTION BOX: N NWNE	Depth(s) Ground WELL'S STATI Pump EST. YIELD	completed Well dwater Encountered IC WATER LEVEL	(1)	below la	(2) and surface r after	hours pum hours pum	ping gpm ping gpm		
W									
S If yes, mo/day/yr sample was submitted									
Water well disinfected? ☐ Yes ☑ No									
Casing height above la TYPE OF SCREEN OR Steel Sta Brass Ga SCREEN OR PERFORA Continuous slot Louvered shutter SCREEN-PERFORATE GRAVEL PAC 6 GROUT MATERIAL Grout Intervals: From What is the nearest source	Glued	mped Welded ft., Diameter in., Weight MATERIAL: PVC None used (open heads a second processed for the second pro	Threaded in	tolbs./ft. Other (S) Drill Other (S) Other (S) Drill Other (S) Other (S) Drill Other (S) Other (S)	led holes or (specify) ft., From ft., From ft., From ft., From Other Other Other Other Other Other Other	iameter	to ft. to ft. ft. to ft. ft. to ft. ft. to ft.		
Direction from well					īīN/A				
FROM TO	LITHOLOG	FIC LOG	FROM	ТО	LITHO. LO	OG (cont.) <u>or</u> PLU	JGGING INTERVALS		
			-						
SEE A	TTACHED LOG								
7 CONTRACTOR'S Ounder my jurisdiction and Kansas Water Well Contunder the business name	I was completed or ractor's License NofMINTER-W	on (mo/day/year)4-24 Io208 This V ILSON DRILLING CO	4-09 ar Vater Well R D., INC	nd this re ecord wa by (si	cord is true to as completed gnature) I	to the best of my l l on (mo/day/year Wara J. Kell	knowledge and belief.) 4-27-09		
INSTRUCTIONS: Use typev (white, blue, pink) to Kansas Telephone 785-296-5522. Se http://www.kdheks.gov/waterw	Department of Health nd one copy to WAT	and Environment, Bureau	of Water, Geole	ogy Section	n, 1000 SW Ja	ckson St., Suite 420,	Topeka, Kansas 66612-1367.		
KSA 82a-1212				Ch	eck: 🗹 Wl	hite Copy, Bl	ue Copy, Pink Copy		

20,893

The Professionals MINTER-WILSON DRILLING CO. Water Systems Complete Installation and Domestic Water Systems Complete Installation

Irrigation and Repairing

INCORPORATED

P.O. Box A • GARDEN CITY, KANSAS 67846 Phone 620-276-8269 •

NAME

TRI-STATE GENERATION - CIRCLE #14

COUNTY

FINNEY

DATE

3-6-09

LOCATION:

NE 1/4 9-25-34 - FROM HOLCOMB LAND & CRIST ROAD -

2-1/2 MILES WEST, 1 MILE SOUTH

& 1/2 MILE EAST

- NORTHEAST EDGE OF CIRCLE

STATIC WATER LEVEL - 230 FT.

TEST #4

O' TO 1' - TOP SOIL

1' TO 18' - FINE SAND - LOOSE

18' TO 30' - BROWN SANDY CLAY

30' TO 61' - FINE TO MEDIUM SAND & GRAVEL

61' TO 89' - BROWN SANDY CLAY

89' TO 96' - FINE TO MEDIUM SAND & GRAVEL

96' TO 119' - SANDY BROWN CLAY WITH LAYERS OF SAND & GRAVEL

119' TO 131' - FINE TO MEDIUM SAND & GRAVEL

131' TO 157' - BROWN CLAY WITH STREAKS OF SAND & GRAVEL

157' TO 291' - FINE TO MEDIUM SAND & GRAVEL WITH LAYERS OF **BROWN & WHITE CLAY**

291' TO 296' - BROWN CLAY

296' TO 307' - FINE TO MEDIUM SAND & GRAVEL

307' TO 328' - BROWN CLAY WITH STRIPS OF SAND

328' TO 335' - FINE TO MEDIUM SAND & GRAVEL

335' TO 376' - BROWN CLAY - STICKY

376' TO 379' - FINE TO MEDIUM SAND & GRAVEL

379' TO 403' - BROWN CLAY WITH STREAKS OF SAND & GRAVEL

403' TO 418' - YELLOW CLAY WITH BROWN SANDY CLAY & BROWN ROCK

418' TO 436' - GRAY SHALE - 300 PULL DOWN - WITH LAYERS OF YELLOW

CLAY & BROWN ROCK - 5%

436' TO 485' - HARD GRAY SHALE & BLACK SHALE - 400 PULL DOWN