WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No.	
1 LOCATION OF WATER WELL:		Section Number Township No. Range Number	
County: FINNEY	1/4 SE 1/4 NE 1/4 NV		
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here			
HOLCOMB-HWY. 50 - 1 MILE SOUTH, 5 MILES WEST, 1 MILE SOUTH, 4,236 FT. NORTH & 2,834 FT. W		Elevation:	
		Datum: WGS 84, NAD 83, NAD 27	
2 WATER WELL OWNER: WHEATLAND ELECTRIC COOP INC RR#, Street Address, Box #: PO BOX 230		VC   Collection Method: ☐ GPS unit (Make/Model:)	
	T CITY, KS 6	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey	
		Est. Accuracy:	
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF	COMPLETED WELL 450	ft	
SECTION BOX: Depth(s) Group	dwater Encountered (1)	ff (2) $ff$ (3) $ff$	
N WELL'S STAT	TIC WATER LEVEL230.5	ft. below land surface measured on mo/day/yr. 4-27-09	
LECT VIELD		ft. after hours pumping gpm	
		ft., and	
		water supply Geothermal Injection well	
Domestic	☐ Feedlot ☐ Oil field	water supply	
│		c-lawn & garden  Monitoring well	
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No  If yes, mo/day/yr sample was submitted			
S If yes, mo/day/yr sample was submitted			
5 TYPE OF CASING USED: V Steel PVC Other			
CASING JOINTS: Glued Cla			
Casing diameter 16 in to 270 ft., Diameter in to ft. Diameter in to ft.			
Casing height above land surface			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)			
SCREEN OR PERFORATION OPENINGS ARE:			
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)			
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)  SCREEN-PERFORATED INTERVALS: From 270			
From ft. to ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 20 ft. to 190 ft., From 250 ft. to 450 ft.			
From ft. to ft., From ft. to ft.			
6 GROUT MATERIAL: ☐ Neat cement ☑ Cement grout ☐ Bentonite ☐ Other			
What is the nearest source of possible contamination:			
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below)			
Sewer lines Cesspoo Watertight sewer lines Seepage	_ ~ ~ _	· -	
☐ Watertight sewer lines ☐ Seepage Direction from well SOUTHEAST		zer storage	
FROM TO LITHOLO			
SEE ATTACHED LOC	j		
7 CONTRACTOR'S OR LANDOWNE	D'S CEDTIFICATION: This	water well was 🗸 constructed 🗆 reconstructed or 🗆 always	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged under my jurisdiction and was completed on (mo/day/year)4-27-09 and this record is true to the best of my knowledge and belief.			
Kansas Water Well Contractor's License No208 This Water Well Record was completed on (mo/day/year) 4-28-09			
under the business name of MINTER-WILSON DRILLING CO., INC. by (signature) The Heller			
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.			
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at			
http://www.kdheks.gov/waterwell/index.html.		Charles Awhite Court Division Division	
KSA 82a-1212		Check: White Copy, Blue Copy, Pink Copy	

23,455

## The Professionals MINTER-WILSON DRILLING CO. Water Systems Complete Installation and Repairing

**INCORPORATED** 

Phone 620-276-8269 • P.O. Box A . GARDEN CITY, KANSAS 67846

NAME

WHEATLAND ELECTRIC - CIRCLE # G7

COUNTY

**FINNEY** 

DATE

3-5-09

LOCATION:

NW 1/4 18-25-34 - DEERFIELD LANE & CRIST ROAD -

2-1/2 MILES SOUTH, 1-1/2 MILES EAST & 1/4 MILE NORTH - 140 FT. NORTH & & 45 FT. WEST OF EXISTING WELL

STATIC WATER LEVEL - 230 FT.

## TEST #1

0' TO	10' - TOP SOIL & FINE SAND
10' TO	20' - SANDY CLAY - BROWN
20' TO	55' - FINE TO MEDIUM SAND & GRAVEL
55' TO	76' - BROWN CLAY & CALICHE
76' TO	108' - FINE TO MEDIUM SAND & GRAVEL
108' TO	124' - BROWN CLAY
124' TO	180' - BLUE & BROWN CLAY
180' TO	260' - FINE TO MEDIUM SAND, SMALL GRAVEL & 15% CLAY
260' TO	300' - MEDIUM TO COARSE SAND & SMALL GRAVEL
300' TO	340' - BROWN CLAY & A LITTLE CALICHE
340' TO	360' - SAND - MEDIUM TO COARSE
360' TO	394' - BROWN CLAY - 20% SAND STREAKS
394' TO	420' - SAND - MEDIUM TO COARSE, SMALL GRAVEL
	- 20% CLAY STREAKS
420' TO	429' - SAND - MEDIUM TO COARSE & MIXED CLAY
429' TO	440' - BROWN CLAY & BROWN ROCK STREAKS
	460' - BROWN & GRAY & YELLOW CLAY
460'TO	500' - SHALE