WATER WELL RECORD	Form WV	VC-5	Division of Water	Resources App. No		
1 LOCATION OF WATER WEI County: FINNEY	1/4 SE 1/4 NW		35	T <b>25</b> S	Range Number R 34	
Street/Rural Address of Well Loc	Global Positioning					
from nearest town or intersection: If at owner's address, check here			Latitude: (in decimal degrees)			
FROM BRIDGE SOUTH OF HOLCOMB - 4 M S, 1 M W, 6 M S,		6 M S,	Longitude: (in decimal degrees)			
1,565 FT. NORTH & 1,428 FT. WEST		Elevation:   Datum:   WGS 84,   NAD 83,   NAD 27				
2 WATER WELL OWNER: WHEATLAND ELECTRIC COOP INC			Collection Method:			
RR#, Street Address, Box #: PO BOX 230		☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey				
City, State, ZIP Code : SCOTT CITY, KS 67871		Est. Accuracy: 3 m, 3-5 m, 5-15 m, >15 m				
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 385						
	SECTION BOX: Depth(s) Groundwater Encountered (1)					
	WELL'S STATIC WATER LEVEL. 220 ft. below land surface measured on mo/day/yr. 4-2-09.					
WELL S	Pump test data: Well water was					
	EST VIELD and Well water was & often house numerica					
NW NE ESI. HE	76 295					
W E Bore Hole	WELL WATER TO BE USED AS: ✓ Public water supply ☐ Geothermal ☐ Injection well					
sw   X <sub>E</sub>   Domestic   Feedlot   Oil field water supply   Dewatering   Other (Specify below)						
Was a chemical/bacteriological sample submitted to Department?  Yes No						
S If yes, mo/day/yr sample was submitted						
1 mile  Water well disinfected? ✓ Yes ☐ No						
5 TYPE OF CASING USED:  Steel PVC Other						
CASING JOINTS: Glued Clamped W Welded Threaded						
Casing diameter16 in. to .BELOW. ft., Diameter ft., Diameter ft.						
Casing height above land surface. 18 in., Weight 62.58 lbs./ft., Wall thickness or gauge No375						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
Steel Stainless Steel			Other (Specify)			
Brass Galvanized Steel None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)						
□ Louvered shutter □ Key punched □ Wire wrapped □ Saw cut □ Other (specify)						
From						
GRAVEL PACK INTERVALS: From 40 ft. to 199 ft., From 219 ft. to 385 ft.						
From ft. to ft., From ft. to ft.						
6 GROUT MATERIAL: ☐ Neat cement ☑ Cement grout ☑ Bentonite ☐ Other						
Grout Intervals: From 0 ft. to 25 ft., From 25 ft. to 40 ft., From ft. to ft.						
What is the nearest source of possible			<b>,</b>			
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)						
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well						
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well						
Direction from well SOUTHEA			om well 27.0.F.T.			
	IOLOGIC LOG	FROM	TO LITHO. LO	OG (cont.) or PLU	GGING INTERVALS	
0 235 PLAIN CASING						
235 340 STAINLESS STE	EL SCREEN					
340 369 PLAIN CASING						
369 379 STAINLESS ST	EEL SCREEN		SEE ATTA	CHED LOG		
379 385 PLAIN CASING						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 🗸 constructed, 🗆 reconstructed, or 🗀 plugged						
under my jurisdiction and was completed on (mo/day/year) 5-15-09						
Kansas Water Well Contractor's Lic	ense No 208 This W	ater Well Red	cord was completed	on (mo/day/year)	5-22-09	
under the business name of MINTER-WILSON DRLG. CO., INC. by (signature) Morai Keller						
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.						
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at						
http://www.kdheks.gov/waterwell/index.html.						
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy						

14,826

The Professionals

## MINTER-WILSON DRILLING CO. Water Systems Complete Installation

and Domestic and Repairing

INCORPORATED

Phone 276-8269

P.O. Box A

**GARDEN CITY, KANSAS 67846** 

NAME

WHEATLAND ELECTRIC

COUNTY

**FINNEY** 

DATE

2-28-08

LOCATION: SE 1/4 35-25-34 - SOUTH ON HOLCOMB LANE - 10-3/4 MILES

& 1/4 OF A MILE WEST TO PIVOT - 270 FT. NORTH & 168 FT. WEST OF

**EXISTING WELL** 

#12 TH - 4-08NW

## STATIC WATER LEVEL -

1' - TOP SOIL 0' TO

1' TO 8' - FINE SAND - LOOSE

8' TO 17' - GRAY CLAY

17' TO 27' - BROWN SANDY CLAY

27' TO 40' - FINE TO MEDIUM SAND & GRAVEL

40' TO 109' - MEDIUM COARSE GRAVEL

109' TO 115' - BROWN CLAY

115' TO 147' - FINE TO MEDIUM SAND & GRAVEL

147' TO 158' - MEDIUM COARSE GRAVEL

158' TO 172' - FINE TO MEDIUM SAND & GRAVEL

172' TO 186' - GRAY CLAY

186' TO 203' - BROWN CLAY - GRAVEL STREAK

203' TO 219' - BROWN BLUE CLAY

219' TO 224' - FINE TO MEDIUM SAND & GRAVEL

224' TO 235' - BROWN CLAY

235' TO 252' - FINE TO MEDIUM SAND & GRAVEL

252' TO 276' - BROWN SANDY CLAY

276' TO 284' - FINE TO MEDIUM SAND & GRAVEL

284' TO 294' - BROWN SANDY CLAY

294' TO 308' - FINE TO MEDIUM SAND & GRAVEL

308' TO 316' - FINE TO MEDIUM SAND & GRAVEL - CLAY STRIPS

316' TO 338' - FINE TO MEDIUM SAND

338' TO 374' - BROWN CLAY

374' TO 378' - FINE TO MEDIUM SAND

378' TO 474' - BROWN CLAY

474' TO 484' - YELLOW CLAY-BROWN ROCK MIXED - TIGHT

484' TO 487' - GRAY SHALE

487' TO 515' - SHALE - HARD PULL DOWN 250