WATER WELL RECORD	Form WWC-5	Division of Wa	ter Resources App. N	26,081		
1 LOCATION OF WATER WELL:	Fraction	Section Number	Township No.	Range Number		
	1/4 NE 1/4 NE 1/4 SW		T 25 S	R 34 □E 🗹 W		
Street/Rural Address of Well Location; from nearest town or intersection: If at c			ng System (GPS) ir	ntormation: (in decimal degrees)		
HOLCOMB-4 M S, 1 M W, 6 M S, 3	· -			(in decimal degrees)		
2,100 FT. NORTH & 2,915 FT. WES		Elevation:				
2 WATER WELL OWNER: WHEAT	LAND ELECTRIC COOP IN	Datum: WGS C Collection Method	84, 🔲 NAD 83, 🔲	NAD 27		
RR#, Street Address, Box #: PO BOX 230		GPS unit (M	GPS unit (Make/Model:)			
City, State, ZIP Code : SCOTT	CITY, KS 67871	Digital Map/I	hoto, Topographi	c Map, ☐ Land Survey		
3 LOCATE WELL			<3 m, ☐ 3-5 m, ☐	3-13 m, <u> </u>		
	COMPLETED WELL4					
SECTION BOX: Depth(s) Ground	Depth(s) Groundwater Encountered (1)					
WELL SSIAII	WELL'S STATIC WATER LEVEL					
EST. YIELDgpm. Well water wasft. afterhours pumpinggpm						
W						
Domostio	TO BE USED AS: Public Greedlot Oil field			njection well		
	☐ Industrial ☐ Domestic					
	bacteriological sample submitte					
	day/yr sample was submitted					
	fected? Yes No					
5 TYPE OF CASING USED: Steel		• •	•••••			
CASING JOINTS: Glued Clam Casing diameter 16 in to 285	nped M Welded L Thre	in to ft i	Diamatar	in to A		
Casing height above land surface12						
TYPE OF SCREEN OR PERFORATION						
✓ Steel ☐ Stainless Steel	□ PVC	Other (Specify)				
☐ Brass ☐ Galvanized Steel SCREEN OR PERFORATION OPENING						
☐ Continuous slot	☐ Gauze wrapped ☐ Torch c		☐ None (open hole			
Louvered shutter Key punched	✓ Wire wrapped ☐ Saw cu	Other (specify).				
SCREEN-PERFORATED INTERVALS:	From ft. to					
GRAVEL PACK INTERVALS:	From 20 ft. to .20	5 ft., From	265 ft.	to 450 ft.		
	From ft. to					
6 GROUT MATERIAL: ☐ Neat ceme Grout Intervals: From 0	ent 🗹 Cement grout 🔲 Be 20 ft., From 205	ntonite		Α		
What is the nearest source of possible conta		II. 10 . II	., From	. II. 10II.		
Septic tank Lateral lin	es Pit privy Livesto		le storage 🔲 Oth	er (specify below)		
Sewer lines Cesspool	Sewage lagoon Fuel st		ed water well			
☐ Watertight sewer lines ☐ Seepage p Direction from well		er storage	,			
FROM TO LITHOLOG				GGING INTERVALS		
SEE ATTACHED LOC				****		
SEE ATTACHED LOG						
7 CONTRACTOR'S OR LANDOWNER	PS CERTIFICATION: This	vater well was [7] cons	ructed 🗆 recorate	ucted or Distanced		
under my jurisdiction and was completed on	n (mo/day/year) 3-2-11	and this record is true	to the best of my k	nowledge and belief		
under my jurisdiction and was completed on (mo/day/year) .3-2-11 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/year) .3-3-11						
under the business name of MINTER-WI		by (signature)				
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at						
http://www.kdheks.gov/waterwell/index.html.	ER WELL OWNER and retain one	or your records. Include i	ee or \$5.00 for each c	onstructed well. Visit us at		
KSA 82a-1212		Check: 🗹 W	hite Copy, 🔲 Blu	ue Copy, Pink Copy		

The Professionals MINTER-WILSON DRILLING CO. Water Systems Complete Installation Complete Installation

Irrigation and Repairing

INCORPORATED

Phone 620-276-8269 P.O. Box A **GARDEN CITY, KANSAS 67846**

NAME

WHEATLAND ELECTRIC - CIRCLE # G56

COUNTY

FINNEY

DATE

10-11-10

LOCATION:

SW 1/4 32-25-34 - HOLCOMB LANE & PARALLEL ROAD -

3-1/2 MILES WEST, 3/8THS OF A

MILE NORTH & 1/8TH OF A MILE WEST

-NORTHEAST EDGE OF CIRCLE

STATIC WATER LEVEL -

TEST #1

0' TO 1' - TOP S	SOII	L
------------------	------	---

1' TO 12' - BROWN SANDY CLAY

17' TO 28' - BROWN CLAY

28' TO 45' - FINE TO MEDIUM SAND

45' TO 130' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

130' TO 155' - BROWN CLAY

155' TO 165' - BROWN CLAY WITH GRAVEL STREAKS

165' TO 181' - FINE TO MEDIUM SAND & GRAVEL

181' TO 191' - BROWN CLAY

191' TO 204' - FINE TO MEDIUM SAND & GRAVEL - CLAY STREAKS

204' TO 218' - BROWN CLAY WITH GRAVEL STREAKS

218' TO 250' - BROWN & BLUE CLAY - STICKY

250' TO 258' - BROWN & BLUE CLAY WITH GRAVEL STREAKS

258' TO 295' - FINE TO MEDIUM SAND & GRAVEL - 10% CLAY

295' TO 333' - BROWN CLAY

333' TO 348' - BROWN SANDY CLAY

348' TO 368' - FINE TO MEDIUM SAND & GRAVEL

368' TO 390' - FINE TO MEDIUM SAND & GRAVEL - 10% CLAY

390' TO 398' - BROWN SANDY CLAY

398' TO 418' - FINE TO MEDIUM SND WITH CLAY STREAKS - 20%

418' TO 428' - BROWN SANDY CLAY

428' TO 440' - BROWN CLAY

440' TO 446' - BROWN CLAY WITH BROWN ROCK MIXED - 30%

446' TO 453' - YELLOW CLAY

453' TO 470' - SHALE - HARD PULL DOWN