WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No. 26,082			
1 LOCATION OF WATER WELL:	Fraction	Section Number Township No. Range Number			
County: FINNEY Street/Rural Address of Well Location	1/4 NW 1/4 NE 1/4 NW  or if unknown distance & direction				
from nearest town or intersection: If a		]. Latitude: (in decimal degrees)			
HOLCOMB-4 M S, 1 M W, 5 M S,	4 M W,	Longitude: (in decimal degrees)			
5,215 FT. NORTH & 3,585 FT. W	EST	Elevation:			
	ATLAND ELECTRIC COOP IN	IC Collection Method:			
O'L GLI GID O 1	FREESE, P O BOX 230	☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
City, State, ZIP Code : SCOT	T CITY, KANSAS 67871	Est. Accuracy: $3 \text{ m}$ , $3 \text{ s}$ m, $3 \text{ s}$ s, $3 \text{ s}$ m, $3 \text{ s}$ s, $3 \text{ s}$ m, $3 $			
3 LOCATE WELL	F COMPLETED WELL37				
		ft. (2) ft. (3) ft.			
N WELL'S STA	TIC WATER LEVEL266	ft. below land surface measured on mo/day/yr9-15-11			
Pur	np test data: Well water was	,ft. after hours pumping gpm			
[==14 M ==   ==14E ==   ] =		ft., after hours pumping gpmft., and in. to ft.			
		water supply Geothermal Injection well			
Domestic	☐ Feedlot ☐ Oil field	water supply			
✓ Irrigation	☐ Industrial ☐ Domestic	c-lawn & garden  Monitoring well			
s If yes, m	al/bacteriological sample submitted				
	sinfected?  Yes  No				
5 TYPE OF CASING USED: St					
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter .16					
			☐ Brass ☐ Galvanized Steel ☐ None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE:		
			☐ Continuous slot     Mill slot     ☐ Gauze wrapped    Torch cut    Drilled holes    ☐ None (open hole)		
			Louvered shutter Key punched Wire wrapped Saw cut Other (specify)  SCREEN-PERFORATED INTERVALS: From 280 ft. to 375 ft., From ft. to ft.		
From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS		10 ft., From 270 ft. to 375 ft.			
6 CROUT MATERIAL: Neat ce	ment Cement grout DR6	entonite			
Grout Intervals: From0 ft	to .20 ft., From .210	entonite			
What is the nearest source of possible co	ntamination:				
Septic tank Lateral Sewer lines Cesspo	lines Pit privy Livest ol Sewage lagoon Fuel s	torage Abandoned water well			
☐ Watertight sewer lines ☐ Seepag	e pit 🔲 Feedyard 🔲 Fertili:	zer storage Oil well/gas well N/A			
Direction from well		ance from well			
FROM TO LITHOLO	OGIC LOG FROM	VI 10 EITHO. EOG (COIL.) OF PLOGGING INTERVALS			
SEE ATTACHED LC	G				
7 CONTRACTOR'S OR LANDOWN	ER'S CERTIFICATION: This	s water well was 🗸 constructed, 🗌 reconstructed, or 🔲 plugged			
under my jurisdiction and was complete	d on (mo/day/year) 9-15-11	and this record is true to the best of my knowledge and belief.			
Kansas Water Well Contractor's License	No. 208 This Water W	'ell Record was completed on (mo/day/year) 9-21-11			
INSTRUCTIONS: Use typewriter or ball point	pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRII</u>	NT clearly. Please fill in blanks and check the correct answers. Send three copie			
(white, blue, pink) to Kansas Department of He	Ith and Environment, Bureau of Water,	Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367; for your records. Include fee of \$5.00 for each constructed well. Visit us a			
http://www.kdheks.gov/waterwell/index.html.	TATION WILLIAM OWNERS AND LONGIN ONE				
KSA 82a-1212		Check: White Copy, Blue Copy, Pink Cop			

## MINTER-WILSON DRILLING CO. Water Systems Complete Installation

Irrigation and Repairing

**INCORPORATED** 

Phone 620-276-8269 P.O. Box A • GARDEN CITY, KANSAS 67846

NAME

WHEATLAND ELECTRIC - CIRCLE # G21

COUNTY

FINNEY

DATE

11-2-10

LOCATION:

NW 1/4 30-25-34 - HOLCOMB & PARALLEL ROAD - 3-1/2 MILES WEST.

1 MILE NORTH, 1 MILE WEST &

7/8THS MILE NORTH

- NORTH EDGE OF CIRCLE

STATIC WATER LEVEL - 250 FT.

## TEST#3

0' TO 1' - TOP SOIL

1' TO 10' - BROWN SANDY CLAY - LOOSE

10' TO 36' - BROWN CLAY

36' TO 90' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

90' TO 108' - BROWN CLAY

108' TO 124' - FINE TO MEDIUM SAND & GRAVEL

124' TO 149' - BROWN & BLUE CLAY

149' TO 165' - FINE TO MEDIUM SAND & GRAVEL - 10% CLAY

165' TO 200' - BROWN CLAY - SMALL GRAVEL STRIPS

200' TO 224' - FINE TO MEDIUM SAND & GRAVEL - 10% CLAY

224' TO 232' - BROWN CLAY

232' TO 299' - FINE TO MEDIUM SAND & GRAVEL - 10% CLAY

299' TO 349' - BROWN CLAY

349' TO 365' - FINE TO MEDIUM SAND & GRAVEL WITH STRIPS OF CLAY

365' TO 399' - BROWN SANDY CLAY

399' TO 423' - BROWN CLAY

423' TO 435' - BROWN YELLOW CLAY

435' TO 442' - BROWN YELLOW CLAY WITH TRACES OF SHALE

442' TO 485' - SHALE - HARD PULL DOWN