WATER WELL RE	COPN	Form W	WC-5	Division of	Water Resources Ap	n No	21,388	
		Fraction	WC-3	Section Num			Range Number	
1 LOCATION OF WATER WELL: County: FINNEY		¼ SE ¼ SE	14 SF 14	8	T 25		R 34 □E ☑W	
	of Well Location:	if unknown, distance &		I				
from nearest town or	Global Positioning System (GPS) information: Latitude:							
	Longitude: - 101.06827 (in decimal degrees)							
HOLCOMB-4 MILE	Elevation:							
3 MILES WEST, 25	Datum: ☐ WGS 84, ☐ NAD 83, ☑ NAD 27							
2 WATER WELL OV	Collection Method:							
RR#, Street Address,	GPS unit (Make/Model: GARMIN ST62							
City, State, ZIP Code	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey							
City, State, ZIP Code : SCOTT CITY, KS 67871								
3 LOCATE WELL			400					
WITH AN "X" IN		COMPLETED WELI						
SECTION BOX:								
N	WELL'S STAT	IC WATER LEVEL	2.5.2 ft.	below land sur	face measured on r	no/da	y/yr 8812	
	Pump	test data: Well water	r was	ft. after	hours	pumpi	ing gpm	
EST VIELD and Well water was A show hours numning and								
w NW NE		neter30in. to .4						
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well								
Downstin Deadlet Doil field water surely Devertoring Deter (Specify below)								
SWSE Domestic Peediot Difficil water supply Dewatering Other (specify below)								
S If yes, mo/day/yr sample was submitted								
	water well disin				•			
5 TYPE OF CASING	USED: Stee	I PVC C	Other				·	
CASING JOINTS:	Glued Clar	mped 🗗 Welded ∣	☐ Threaded	Į				
CASING JOINTS: Glued Clamped W Welded Threaded Casing diameter 16 in. to								
Casing thumbter	and surface 12	in Weight	42.05	lhs/ft Wa	ll thickness or gan	ge No	.250	
Casing height above land surface. 12								
	ainless Steel			Other (Specify)				
₩ steet St	Almiess Steel	☐ None used (open he	olo)	Other (Specify)		•••••	•••••	
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☑ Wire wrapped ☐ Saw cut ☐ Other (specify)								
SCREEN-PERFORATED INTERVALS: From								
From								
CD 41777 D 4 C		rrom1	T. TO	π., Fr	om	π. α	ο π.	
GRAVEL PAC	KINIEKVALS:	From						
		From						
6 GROUT MATERIA	L: 🔲 Neat cem	ent 🗹 Cement grout	☐ Benton	nite \square Other		• • • • • • •		
			200	ft. to . 450	ft., From	• • • • • • •	ft. toft.	
What is the nearest source	e of possible cont	amination:						
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below)								
☐ Sewer lines	Cesspool		🔲 Fuel storag		doned water well	NI/A		
■ Watertight sewer			Fertilizer s			N/A		
Direction from well.			Distance	from well		• • • • • • •	••••	
FROM TO	LITHOLOG	GIC LOG	FROM	TO LITH	O. LOG (cont.) or	PLU	GGING INTERVALS	
	×			ĺ				
T CEE /	ATTACHED LOG	1	 					
SEE P	THACHED LOG		+					
								
			1	-				
			$\downarrow \qquad \downarrow$					
			1					
			†	1				
T CONTRACTORS OR LANDOWNERS CERTIFICATION. This was well as The second of the second o								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged								
under my jurisdiction and was completed on (mo/day/year) 8-8-12 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No208 This Water Well Record was completed on (mo/day/year)8-9-12								
under the business name of MINTER-WILSON DRILLING CO., INC. by (signature) TOPIGE K RELIEF								
INSTRUCTIONS: Use ty pewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Depar tment of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 666 12-1367.								
(white, blue, pink) to Kansas Telephone 785-296-5524. Se	Depar timent of Health	n and E nytronment, Bureau	or water, Geol	ogy Section, 1000	ow Jackson St., Suite	420, 1	opeka, Kansas 666 12-1367.	
http://www.kdheks.gov/water	well/index html	IEK WELL OWNER AND I	cam one for	your records. The	uue <u>155</u> 01 \$3.00 101 6	acii c <u>ol</u>	isaucteu wen. VI Sit us at	
KSA 82a-1212				Check:	White Copy.	Blu	e Copy, Pink Copy	
				JJun.	··· ~~₽J, L		, <u> </u>	

The Professionals MINTER-WILSON DRILLING CO. Under Systems Complete Installation and Domestic Water Systems Complete Installation

Irrigation and Repairing

INCORPORATED

P.O. Box A • GARDEN CITY, KANSAS 67846 Phone 620-276-8269 •

NAME

WHEATLAND ELECTRIC - CIRCLE # F12

COUNTY DATE

FINNEY 4-19-12

LOCATION:

SE 1/4 8-25-34 - COUNTY LINE & CRIST ROAD - 1-1/2 MILES EAST,

2 MILES SOUTH & 1/2 MILE EAST - SOUTHEAST EDGE OF CIRCLE

STATIC WATER LEVEL - 230 FT.

TEST#2

0' TO 7' - SAND

7' TO 13' - BROWN SANDY CLAY

13' TO 58' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

58' TO 66' - BROWN SANDY CLAY

66' TO 82' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

82' TO 92' - BROWN SANDY CLAY

92' TO 97' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

97' TO 105' - BROWN SANDY CLAY

105' TO 112' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

112' TO 150' - BROWN SANDY CLAY

WITH LAYERS OF SAND & GRAVEL

150' TO 195' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE WITH LAYERS OF BROWN SANDY CLAY

195' TO 200' - BROWN CLAY

200' TO 210' - BLUE CLAY

210' TO 245' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN SANDY CLAY - 20%

245' TO 255' - FINE TO MEDIUM SAND & GRAVEL

& BROWN SANDY CLAY LAYERS - 50/50

255' TO 266' - BROWN SANDY CLAY

266' TO 278' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN SANDY CLAY - 15%

278' TO 281' - BROWN SANDY CLAY

281' TO 295' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN SANDY CLAY - 20%

295' TO 311' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

311' TO 318' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

WITH 30% WHITE ROCK

318' TO 335' - BROWN SANDY CLAY

WITH STRIPS OF WHITE ROCK

335' TO 347' - FINE TO MEDIUM SAND & SMALL GRAVEL

WITH STRIPS OF WHITE ROCK - 25%

347' TO 357' - BROWN SANDY CLAY

357' TO 360' - FINE TO MEDIUM SAND

360' TO 381' - BROWN SANDY CLAY

381' TO 390' - BROWN, YELLOW & WHITE CLAY WITH 20% BROWN ROCK

390' TO 400' - BROWN, YELLOW & WHITE CLAY WITH 10% BROWN ROCK

400' TO 410' - SHALE - BROWN & YELLOW CLAY WITH 10% BROWN ROCK

410' TO 420' - SHALE WITH 20% BROWN ROCK

420' TO 440' - SHALE - 250 PULL DOWN