USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

## WATER WELL RECORD KSA 82a-1201-1215

		_	_			_	_
T	R	EW	sec	1/4	1/4	1/4	No.

Kansas State Dept. Of Health (Water Well Contractors) Forbes–Bldg. 740 Topeka, Kansas 66620

										_	
1 Location of well:	County	Township name	Fraction		Section	on number		Town number	Range number		
	Kearny	Southside	NW of		<u> </u>	6		TS 25	RW 35	-	
Distance and direction from nearest town or city: 4 miles soutn & 3 Owner  3 miles west of Deerriela, Ks.  Street address of well location if in city:  Address					Conden City Va nowhy						
					ess:						
Locate with "X" in section below: Sketch map:							4 Well depth: 300 ft. Date of completion 1-14- Well diameter 20 in.				
	1 1 1					5 Cable tool Rotary Driven			Driven Dug	1	
							6 Use: Domestic Public supply Industry  X Irrigation Air conditioning Commercial				
w	E										
iixi							7 Casing: Material StellHeight: above/below-				
							Threaded Welded Susurface 12 in.				
<u> </u>	S —→1 Mile						Diam. Weight 54-27bs./ft. 1  16_ in. to551 ft. depth!Drive shoe? ☐ Yes ▼ No				
2	Туре	e and color of material			From	То	in. toft. depth				
m a :-							Mai				
Top Soil,	Fine Sand				0	5	Type Dia Slot/gauze Length				
Sand & Gr	ravel Coarse (	Loose)			_5_	57	Set	Set between ft. and ft Permitings: 120-145,205-260,290-55			
Sandy Cla	ıy				57	7)1		Size range of material <b>[2]</b>			
Fine to N	Medium Sand &	Gravel (Loos	-1		7և	95		tic water level: ft. below land surface	Date 4-14-7		
Fine to Medium Sand & Gravel (Loose) Clay					95	128	10 Pumping level below land surfaces:  20 ft. after 2 hrs. pumping 021 g.p.m.				
	. C					11,5	6. 5.				
Very Fine Sand (Loose)					28	1-4.7	Esti	200 g.p.m.	4		
Clay					145	208	11 Water sample submitted:  Yes X No Date				
Fine to Medium Sand & Gravel (Locse)					208	215	12 Well head completion:  Pitless adapter  12 Inches above grade  13 Well grouted? XX Yes No  Neat cement Bentonite X Clay Pugg  Depth: From Uft. to 10 ft.				
Sandy Clay 50% Sand to Gravel					215	243					
Fine to Medium Sand & Gravel (Loose)					243	260					
Sandy Clay					260	280	14 Ne	ntamination: N/A			
Bery Fine Sand (Loose)					280	290	ft Direction Type _ Well disinfected upon completion? [ Yes				
							15 Pum	np: [ nufacturer's name <u>FMC</u>	Not installed		
					290	330	Model number 5020 HP 100 Volts Length of drop pipe 140 ft. capacity 800 g.m.				
Fine to Medium Sand & Gravel 30% Clay					330	350	Len Typ		t. capacity QQQ g.m.p.	1	
Yellow					350	365	- =	_	Turbine Reciprocating		
	· · · · · · · · · · · · · · · · · · ·	a second sheet if needed)						Certrifugal [	Other		
16 Remarks: elevati	Good well.							ter well contractor's certifi s well was drilled under my			
Topography: No Possible Contamination.							report is true to the best of my knowledge and belief Minter-Wilson Drig. Co. 2				
□HiII							Busi	ness name	License No.	:	
IX Slope ☐ Upland							1	dress Box 445 Gar	Date 3/13/	*s-	
Valley								Authorized represe	ntdti∜e ′		