USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| | County | Fraction | | Section number | | Township number Range number | | | |
|---|--|---------------------------|-------------------------|--|---|---|---|----------------------|--|
| 1. Location of well: | KEARNY | | | | | т 25 s | r 35 | # /w | |
| | ection from nearest town or city: Ac | | l | ner of well | | iple T Farms | | | |
| bridge at I Street dudress of wel | Deerfield 1 east 7 Hoodion if in city: $rac{1}{2}$ north | south 14 west | | street: tate, zip | | ircle #13-3) kmin,Ks 67869 | | | |
| 4. Locate with "X" in section below: N | | | | | 6. Bore hole dia. 26 in. Completion date 11. Well depth 386 ft. | | | 11-3 0-7 | |
| - NW NE | | | | | | 7 Cable tool Rotary Driven Dug Hollow rod Jetted Bored 圣 Reverse rotary | | | |
| E SE | | | | | | 8. Use: Domestic Public supply Industry Irrigation Air conditioning Stock Lawn Oil field water Other 9. Casing: Material Stephight: Above or below Threaded Welded Surface 12 in. | | | |
| | | | | | | | | | |
| 5. Type and color of material | | | | From | То | Diafn. toft. depth Wall Thickness: inches or | | | |
| | A CONTRACTOR OF THE CONTRACTOR | | | | | 10. Screen: Manufacturer's a Jojunson of Galv. | | | |
| | | | | | | " | _ Dia _ Length | | |
| | | | | | D _O | • | ft. and 3(| 00_ft. | |
| | | | | | 1.6 | Gravel pack? Yes Size ra | nge of material | Down | |
| | | | | | | 11. Static water level:66ft. below land sur | | ./day/yr. | |
| | | | | | | 12. Pumping level below land | Leurfesse | O _{g.p.m} . | |
| | · | | | | | ft. after h | rs. pumping | g.p.m. | |
| | | | | | | Estimated maximum yield | | g.p.m. ./day/yr. | |
| | | | | | | | Date | .,, 33,, , | |
| | | | | | | 14. Well head completion: | | | |
| | | | | | | Pitless adapter 15. Well grouted? yes | Inches above | grade | |
| | | | | | | With:Neat cement Depth: From ft. to | | Concrete | |
| | | | | | | 16. Nearest source of possible | e contamination: | N/A | |
| | | | | i | | Well disinfected upon comple | | No | |
| | | | | | | Manufacturer's name | Ids US Pur | | |
| | | | | | | Model number 2157 Length of drop pipe 160 | HP <u>100</u> Vo ft. capacity <u>120</u> | Ωg.p.m. | |
| | | | | | | Type: Submersible Jet | <u>X</u> Turbin Recip | ne rocating | |
| | (Use a second s | sheet if needed) | | | 1 | Centrifugal | Other | - 1 10 | |
| 18. Elevation: | 19. Remarks: | | | ¥ 1978 | | 20. Water well contractor's o | | is report | |
| Topography: | | | | EIVE EIVE | | s true to the best of my know Minter Wilson | n Drilling | | |
| Hill Slope | Busine Piper | | | | | | Jarden Citt | renies No. | |
| Upland Valley | | | 1.45° (.3 3 3 .75 | د آوانه داده داده | ラ | Authorized rep | Page Bate | 3-76 | |
| Forward the white, bl | lue and pink copies to the Department | of Health and Environment | | \$ 45 E) | | | Form W | WC- 5 | |

Professionals MINTER-WILSON DRILLING CO. Complete histallation and Repairing

 P.O. Box 493
 GARDEN CITY, KANSAS 67846 Phone 276-8269

> Triple T. Farms Kearny County 10-11-75

| Location: | | SW 13-25-35 | | | | | | | |
|-----------|-----|--|--|--|--|--|--|--|--|
| | | Circle 13-3 Pivot | | | | | | | |
| | | 11100 | | | | | | | |
| 0 | 12 | Fine Sand | | | | | | | |
| | 52 | Med to Coarse Gravel (Loose) | | | | | | | |
| | 80 | Brown Clay | | | | | | | |
| | 143 | | | | | | | | |
| 143 | 172 | Fine to Med. Sand & Gravel, 10% Clay (Loose) | | | | | | | |
| | 215 | | | | | | | | |
| | 232 | | | | | | | | |
| | 245 | | | | | | | | |
| | 297 | | | | | | | | |
| | 326 | | | | | | | | |
| | 340 | | | | | | | | |
| | 368 | | | | | | | | |
| | 375 | | | | | | | | |
| | 380 | | | | | | | | |
| | 386 | | | | | | | | |
| | 414 | | | | | | | | |
| 414 | 425 | Brown, Gray & Yellow Clay (Hard) | | | | | | | |
| | | | | | | | | | |

TD 386'