


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County KEARNY	Fraction SE 1/4 NW 1/4 SE 1/4	Section number 16	Township number T 25 S	Range number R 35 E/W	
2. Distance and direction from nearest town or city: Across river bridge at Deerfield 1 1/2 east 7 south 3/4 west Street address of well location if in city: 1 1/2 north		3. Owner of well: Triple T Farms (Circle #164) City, state, zip code: Lakin, Ks 67869				
4. Locate with "X" in section below: 		Sketch map:		6. Bore hole dia. 26 in. Completion date 11-30-75 Well depth 410 ft.		
5. Type and color of material		From		To		7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary
						8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other
						9. Casing: Material steel Weight: Above or Below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 36.87 lbs./ft. Dia. 16 in. to 417 depth, Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth, gage No. 219 MNC
						10. Screen: Manufacturer's name Johnson Division Type Galv Dia. 16 1/2 Slot/gauze 100 Length 20 Set between 250 ft. and 270 ft. Perf. 120-250 ft. and 335-410 ft. Gravel pack? yes Size range of material 20 1/2" Down
						11. Static water level: <input type="checkbox"/> mo./day/yr. 79 ft. below land surface Date 12-3-76
				12. Pumping level below land surfaces: 117 ft. after 2 hrs. pumping 768 m. 112 ft. after 4 hrs. pumping 1280 g.p.m. Estimated maximum yield 1280 g.p.m.		
				13. Water sample submitted: <input type="checkbox"/> mo./day/yr. Yes <input checked="" type="checkbox"/> No Date <input type="checkbox"/>		
				14. Well head completion: <input type="checkbox"/> Pitless adapter 12 inches above grade		
				15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.		
				16. Nearest source of possible contamination: N/A ft. <input type="checkbox"/> Direction <input type="checkbox"/> Type <input type="checkbox"/> Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		
				17. Pump: Not installed Manufacturer's name Goulds US Pumps Model number K2226 HP 100 Volts <input type="checkbox"/> Length of drop pipe 160 ft. capacity 1200 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
				20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Minter Wilson Drilling 208 Business name P.O. Box A Garden City, Ks License No. 8-3-76 Address _____ Date 8-3-76 Signature _____ Authorized representative		
18. Elevation: Topography: <input type="checkbox"/> Hill <input checked="" type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley	19. Remarks: (Use a second sheet if needed)					

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5

Phone 276-8269 • P.O. Box 493 • GARDEN CITY, KANSAS 67846

Triple T. Farms
Kearny County
10-7-75

Location: SE 16-25-35
Circle 16-4

Test # 4 Pivot

0	31	Fine Sand
31	97	Med. To Course Gravel
97	128	Brown Clay
128	140	Brown Clay, Streaks of Gravel, 35%
140	155	Blue Clay
155	186	Fine to Med. Sand & Gravel (Loose)
186	200	Brown Clay, Small Streaks of Gravel, 20%
200	271	Fine to Med. Sand & Gravel (Loose)
271	335	Brown Clay
335	348	Fine to Med. Sand & Fine Gravel, 10% Clay (Loose)
348	380	Fine to Med. Sand & Gravel (Loose)
380	410	Fine to Med. Sand & Fine Gravel, 10% Clay (Loose)
410	428	Brown & Gray Clay, 20%, Streaks of Fine Gravel (Tight)
428	440	Brown, Gray & Yellow Clay (Hard)

TD 410'