USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

## WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

F-10

	County	Fraction	s	ection n	number	Township number	Range nur 'ar	1	
1. Location of well:	KEARNY	NE <sub>14</sub> SW 1/4 NE	1/4	20		<sub>1</sub> 25	3 <b>5</b>	v I	
2 Distance and disca				of well.	May.	1 .	<u> </u>	7	
2. Distance and direction from nearest town or city: From Takin s south 3. Owner of well: Woyne Thornbrough east 3 south 1 3/4 east 4 south R.R. or street: 45 Laurel St.									
Street address of well location if in city:				City, state, zip cod Concord, Mass. 01742					
			City, sidile	e, 21p cc		6. Bore hole dia. 26 in.		176	
4. Locate with "X" in section below: Sketch map:						Well depth 370ft.	Completion date	4-110	
ī [ ·	<del></del>							극	
1	ا اس		1			7 Cable tool Rotary			
NW    \( \sigma \)							BoredReverse rota	7	
W   I   E						8. Use: Domestic Pu			
ž W I I I I E						X Irrigation Air conditioning Stock Lawn Oil field water Other			
sw	SE					9. Casing: Material Peight: Above or below			
s					Threaded Welded Surface in.  RMP PVC Weigh 6 . 87 lbs ./ft.				
1 1 Mi	ile ————					Dia ] 6 in. to 371 ft. dep	th Wall Thickness: inches or		
5. Type and color of	material			From	To	Dia in. to ft. dept	h gage No.	=	
						10. Screen: Manufacturer's n	Sion .	-	
						_ Galv.	16 <sup>11</sup>	-	
						Slot/gauze 100		_	
						Set between 330	ft. and 350	it.	
				Ī	P	pf. 120-330_ft. o	ind 350-370	t.	
						Gravel pack? <u>FOS</u> Size ra	nge of material	<u>co</u> n	
						11. Static water level:	mo./day/y	т.	
						_67ft. below land sur	face Date 1-22-76	=	
						12. Pumping level below land			
						98 ft. after 3 - 1			
						ft. after	g.p.r		
						13. Water sample_submitted:	mo./day/y	_	
						Ž.	Date	_	
			1			14. Well head completion:	7.0	7	
						Pitless adapter	12 Inches above grade		
						15. Well grouted?		1 100	
						With: Neat cement BentoniteX Concrete			
						Depth: From ft. to .			
						16. Nearest source of possible			
						ft Direction Well disinfected upon comple	**	- Vo	
			$\longrightarrow$			17. Pump:	Not installed		
						Manufacturer's name		2 7/.	
						Model number 12 IB	HPOOolts	1 16	
						Length of drop pipe 160	_ ft. capacity <u>1000</u> в.р.п	·.   🔞″	
			ŀ			Туре:	· ·		
	the Constant					Submersible	X Turbine Reciprocating	1 1	
	(Use a second s	heat if needed)	ı			Jet Centrifugal	Other	1811/2	
10. 51	19. Remarks:					20. Water well contractor's o		ا ْ ا∂	
18. Elevation:	17. Kemarks:					This well was drilled under m			
						is true to the best of my know			
Topography:						Minter Milson D		-   z   j	
Hill Y						Garden City KS	0.   4		
Slope					~	Address	× .	15/5	
Upland						Signed Authorized rep	resentative	作:1	
Valley							//	7,16	
Forward the white, blu	ue and pink copies to the Department	of Health and Environment					Form WWC-5	1.1	

## Irrigation and Domestic Water Systems CO. Complete Installation and Repairing

P.O. Box 493 . GARDEN CITY, KANSAS 67846 Phone 276-8269 •

> THORMBOUGH (FLETCHER) 3-1-76

LOCATION: NE 20-25-35

30 Feet Bast Of Pivot

## STATIC WATER LEVEL: 80.

TEST	#F10	
0	3	Top Soil
3	12	Brown Sandy Clay
12	8 <b>2</b>	Fine To Hed. Sand & Gravel (Loose)
82	100	Brown Sandy Clay
100	142	Fine To Led. Sand & Gravel, Streaks Of Clay (10%)
142	154	Fine To hed. Sand & Gravel, Streaks Of Clay (20%)
154	175	Fine To Med. Sand & Gravel, Streaks Of Clay (10%)
175	181	Brown Sandy Clay
131	230	Fine TW Med. Sand & Gravel (Loose)
230	277	Fine To Med. Sand & Gravel, Streaks Of Clay (10%)
277	316	Brown Sandy Clay
316	350	Fine To Med. Sand & Gravel (Loose)
350	370	Fine To Med. Sand & Fine Gravel, Streaks Of Clay (10%)
3 <i>7</i> 0	395	Fine To Med. Sand, Streaks Of Clay (15%) Tight
<b>39</b> 5	400	Brown, Yellow Clay (Hard, Used Pull Down)