WATER W	ELL R	ECORD	Form WWC-	5	Divisio	n of Water	r Resources; App. No.	21389		
1 LOCATI County:	1 LOCATION OF WATER WELL:		Fraction NE 1/4 NE 1/4				Township Number T 25 S	Range Number R 35 EW		
Distance a	Distance and direction from nearest town or city street address of well if						Global Positioning Systems (decimal degrees, min. of 4 digits)			
located w	located within city? See below				Latitude:					
					Longitude:					
2 WATER WELL OWNER: Cynthia & Dale Yost RR#, St. Address, Box # : Rt. 2 - Box 17E				1	Elevation:					
	Address, E te, ZIP Co				Datum:					
			nsas 67860		Data Col		Method:			
3 LOCATE		6 4 DEPTH OF COMP	LETED WELL	380.	•••••	ft.				
LOCATI		D 4() C 1 (***	T			(2)	Α (2)	£.		
	N "X" IN Depth(s) Groundwater Encountered (1)									
	WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr									
							ft. after hours pumping gpm			
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well										
w NW	1 1 December 1 1 December 1 Decem									
	(2) Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well									
sw	SW SE									
	ī	Was a chemical/bacteri								
Sample was submitted										
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped										
		SUSED: 5 Wrought I				CASINO				
1 Steel 2 PVC		MP (SR) 6 Asbestos-		(specify	below)		Threaded	XX		
Plank assing	, 4 A. r diameter	BS 7 Fiberglass 7	ft Diameter		 . to	ft	Diameter Tilleaded	in to ft		
Blank casing diameter 16 in to 245 ft., Diameter in to ft., Diameter in to ft. Casing height above land surface 12 in., Weight 42.05 lbs./ft. Wall thickness or guage No250										
TYPE OF SCREEN OR PERFORATION MATERIAL:										
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify)										
2 Brass 4 Galvanized Steal 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)										
SCREEN OR PERFORATION OPENINGS ARE:										
1 Continuous slot. (3) Mill slot 5 Guazed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)										
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)										
SCREEN-PERFORATED INTERVALS: From										
GRAVEL PACK INTERVALS: From. 20 ft. to 170 ft., From 230 ft. to 380 ft.										
From										
6 GROUT MATERIAL: 1 Neat cement (2)Cement grout 3 Bentonite 4 Other										
	MATERIA	AL: 1 Neat cement (2)	Cement grout 3 Be	ntonite	4 Other					
Grout Interva		From ft. to	,	†.(N	tt. to4.7.	y It	., From	n. ton.		
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify										
	er lines			1 Fuel sto			andoned water well	below)		
		er lines 6 Seepage pit			er Storage		l well/gas well			
							N/A			
FROM 7	О	LITHOLOGIC	LOG	FROM	TO		PLUGGING INTI	ERVALS		
		**								
			al-i- 1							
		om south side of L								
	south, 7½ miles east, 2 miles south, 1 mile east, 2,150 ft. north									
		515 ft. west	2,150 It. Holt	†						
		See attached	log							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged										
under my jurisdiction and was completed on (mo/day/year) .7-8-06										
Kansas Water Well Contractor's License No 208 This Water Well Record was completed on (mo/day/year)										
under the business name of Minter-Wilson Drilling Co., Inchy (signature) Toro Kelley INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top										
three copies to l	Kansas Depa	rtment of Health and Environmen	t, Bureau of Water, Geolo	gy Section,	1000 SW Ja	ckson St., S	Suite 420, Topeka, Kansas	66612-1367. Telephone		
three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at										
http://www.kdh	e.state.ks.us/	geo/waterwells.								

MINTER-WILSON DRILLING CO.

Irrigation
and Domestic
Water Systems
Complete Installation
and Repairing

INCORPORATED

Phone 276-8269 • P.O. Box A • GARDEN CITY, KANSAS 67846

Dale Yost Kearny County 6-17-06

Location: SE½ 12-25-35 - Deerfield Lane - 5 miles south, ½ mile east, ¼ mile south & ½ mile east to well - ½ mile northeast

Static Water Level - 210 ft.

Test #3

390' to 410' - Shale

0' to 1' - Top soil 1' to 31' - Fine sand - loose 31' to 50' - Fine to medium sand & gravel 50' to 95' - Medium coarse gravel 95' to 103' - Brown clay 103' to 117' - Fine to medium sand & gravel 117' to 136' - Brown clay 136' to 147' - Fine to medium sand & gravel 147' to 155' - Brown clay 155' to 168' - Fine to medium sand & gravel 168' to 193' - Brown gray clay 193' to 196' - Fine to medium sand & gravel 196' to 209' - Brown clay 209' to 213' - Fine to medium sand & gravel 213' to 232' - Brown clay 232' to 237' - Fine to medium sand 237' to 246' - Brown clay 246' to 260' - Fine to medium sand & gravel - 10% clay 260' to 282' - Fine to medium sand & gravel 282' to 303' - Brown clay 303' to 308' - Fine sand 308' to 322' - Fine to medium sand & gravel 322' to 359' - Brown clay 359' to 365' - Fine to medium sand & gravel 365' to 376' - Brown clay - tight 376' to 390' - Brown yellow red clay - hard