WATER WELL REC	ORD	Form W	WC-5	Division of W	Vater Resources App. N	24,382		
1 LOCATION OF WAT		Fraction	*****	Section Number	<del></del>	Range Number		
County: KEARNY		1/4 SW 1/4 NV	V 1/4 NW 1/4	20	T 25 S	R 35 □E 🗹 W		
Street/Rural Address of	Well Location;	if unknown, distance &	& direction	Global Position	ing System (GPS) is	nformation:		
from nearest town or int	ersection: If at	owner's address, check	k here .	Latitude:		(in decimal degrees)		
SOUTH SIDE OF LAI	KIN-1 M. S., 1/	4 M. E. TO LAKIN L	ANE.			(in decimal degrees)		
4 M. S., 4 M. E., 4205		,		Elevation:				
2 WATER WELL OWN			LOT	<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, ☐ NAD 27				
RR#, Street Address, Bo		OUSE FAMILY TRI		Collection Method:  GPS unit (Make/Model:)				
City, State, ZIP Code	R FLETCHER-DRAWER C		☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey					
City, State, Zir Code	· LAKIN,	KANSAS 67860		Est. Accuracy:	] <3 m,	15-15 m. $\square > 15$ m		
3 LOCATE WELL						, r . r		
WITH AN "X" IN	4 DEPTH OF	COMPLETED WEL	L 390		ft.			
SECTION BOX:	Depth(s) Ground	iwater Encountered	(1)	ft. (2)	ft.	(3) ft.		
N I	WELL'S STAT	IC WATER LEVEL	.200ft.	below land surfa	ce measured on mo/o	lay/yr5-27-10		
	Pump	test data: Well water	er was	ft. after	hours pum	ping gpm		
X <sub>NW</sub> NE	EST. YIELD	gpm. Well water	r was	ft. after	hours pur	ping gpm		
W		eter30in. to .						
	WELL WATER	TO BE USED AS: [	Public wat	er supply	Geothermal [1]	Injection well		
	☐ Domestic					Other (Specify below)		
	Irrigation							
		bacteriological sample			🗌 Yes 🗹 No			
S		day/yr sample was sul						
mile	Water well disin	fected? Tyes 🔽	No					
5 TYPE OF CASING US	ED: V Stee	PVC 🗆	Other					
CASING JOINTS: G								
Casing diameter16					Diameter	in to ft		
Casing height above land	surface 12	in., Weight	42,05	lbs./ft., Wall	thickness or gauge N	o250		
TYPE OF SCREEN OR PI	ERFORATION	MATERIAL:		,				
✓ Steel	less Steel	☐ PVC		Other (Specify)				
		None used (open h	iole)					
SCREEN OR PERFORAT			_	_	_			
Continuous slot	Mill slot	Gauze wrapped		Drilled holes	☐ None (open hol	le)		
Louvered shutter	Key punched	Wire wrapped	Saw cut	Other (specify	)			
SCREEN-PERFORATED	INTERVALS:	From299	II. 1099U	n., Fron	1 II.	to It.		
CDAVEL DACK	INITEDMALE.	From 20	11. to	IL, Fron	1 IL. - 240	to ft. to .390 ft.		
GRAVEL FACE								
CDOUT MATERIAL.	□ Most some	nt Coment cross	t Domton	ita Dothan	1 II.	to ft.		
<b>6 GROUT MATERIAL:</b> Grout Intervals: From	0 ft to	20 ft From	. 180	e to 240	A E	Α		
What is the nearest source of	of nossible cont	mination	1: !	ii. io <del></del>	it., Fioiii	11. 10		
Septic tank		nes Pit privy	Livestock p	ens 🗍 Insectio	side storage	per (specify below)		
Sewer lines	Cesspool	Sewage lagoon	Fuel storage	Abandoned water well				
Watertight sewer line			Fertilizer st		A1/A			
Direction from well								
FROM TO	LITHOLOG	IC LOG	FROM			JGGING INTERVALS		
SEE ATT	TACHED LOG							
	· · · · · · · · · · · · · · · ·							
			<del>                                     </del>					
7 CONTRACTOR'S OR	LANDOWNEE	'S CERTIFICATIO	N. This water	r well was 🗖 ass	etructed   record	noted or Daluaced		
under my juriediation and u	vas completed o	n (molday/year) 5-27	-10 an	d this record is to	ue to the best of my	rowledge and halief		
under my jurisdiction and was completed on (mo/day/year) 5-27-10 and this record is true to the best of my knowledge and belief.  Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/year) 5-28-10								
under the business name of MINTER-WILSON DRILLING CO., INC. by (signature) Mental Keller/								
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies								
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Telephone 785-296-5522. Send	one copy to WAT	ER WELL OWNER and	retain one for y	our records. Include	fee of \$5.00 for each of	constructed well. Visit us at		
http://www.kdheks.gov/waterwell/	index.html.			01 1 🗔	WILL CO	0		
KSA 82a-1212				Check:	White Copy, D	ue Copy, Pink Copy		

## The Professionals MINTER-WILSON DRILLING CO. Water Systems Complete Installation

and Repairing

**INCORPORATED** 

Phone 620-276-8269 • P.O. Box A • GARDEN CITY, KANSAS 67846

NAME

FLETCHER RANCH - CIRCLE # A 7

COUNTY

**KEARNY** 

DATE

4-13-10

LOCATION:

NW 1/4 20-25-35 - TATE LANE & PARALLEL ROAD - 1-1/2 MILES WEST,

2-3/4 MILES NORTH & 1/4 MILE WEST TO PIVOT

- 1/8TH MILE NORTHWEST

STATIC WATER LEVEL - APPROX. 200 FT.

## TEST #4

n'	TO	6' -	FINE	SANE	)
v		U -	1114	. Олічь	•

6' TO 11' - BROWN SANDY CLAY

11' TO 48' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

48' TO 56' - BROWN SANDY CLAY

86' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

86' TO 129' - BROWN CLAY WITH LAYERS OF SAND & GRAVEL

129' TO 181' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN CLAY

181' TO 195' - BROWN, GRAY & BLUE CLAY

195' TO 210' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN & BLUE CLAY

210' TO 218' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN & WHITE CLAY-SOME WHITE ROCK

218' TO 252' - BROWN SANDY CLAY WITH STRIPS OF SAND & GRAVEL

252' TO 273' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN & WHITE CLAY 20%

273' TO 306' - BROWN & WHITE CLAY

WITH STRIPS OF WHITE ROCK & SAND 10%

306' TO 317' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN SANDY CLAY 30%

317' TO 327' - BROWN CLAY WITH STRIPS OF WHITE ROCK

327' TO 338' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN CLAY 15%

338' TO 368' - BROWN CLAY WITH STRIPS OF WHITE ROCK

368' TO 373' - FINE TO MEDIUM SAND & GRAVEL

373' TO 410' - BROWN CLAY

410' TO 437' - BROWN SANDY CLAY WITH STRIPS OF SAND 10%

437' TO 440' - HARD BROWN CLAY

440' TO 451' - HARD BROWN & YELLOW CLAY WITH 10% BROWN ROCK - 300 PULL DOWN

451' TO 459' - HARD BROWN & YELLOW CLAY & GRAY SHALE

459' TO 500' - GRAY & BLACK SHALE - SOME BROWN CLAY - 300 PULL DOWN