WATER	WELL RE	CORD	Form WV	VC-5			Resources App. N		
	TION OF W.	ATER WELL:	Fraction 1/4 NE 1/4 SE	1/4 SW 1/4		n Number <b>32</b>	T 25 S		
Street/l	Rural Address	of Well Location; i	f unknown, distance &	direction	Global	Positioning	System (GPS) in	nformation:	
from n	earest town or	intersection: If at o	owner's address, check	here 🔲.	Latitud	le:37.83	3113	(in decimal degrees)	
LAKII	N-S SIDE - 1	M S. 1/4 M E TO	LAKIN LANE, 6 M S,	4 M E,				(in decimal degrees)	
900 F	T. NORTH 8	3,125 FT. WEST	•		Elevat	ion:		 1 NAD 27	
	ER WELL O			OT.	O 11 4	X / . 41	4, 🔲 NAD 83, 🗸		
	Street Address		IOUSE FAMILY TRU		Collect	ion Method:	ce/Model: GARM	IN 62ST	
	State, ZIP Cod		5TH AVESUITE D.	#312		igital Map/Ph	oto. Topographi	ic Map, Land Survey	
City, i	State, ZIF Cou	· DELRA	Y BEACH, FL 33483		Est. Ac	curacy:	3 m, 3-5 m,	] 5-15 m,	
3 LOCA	TE WELL		<u> </u>						
	AN "X" IN	4 DEPTH OF	COMPLETED WELL	,500		ft.			
SECTI	ON BOX:	X: Depth(s) Groundwater Encountered (1)							
	N WELL'S STATIC WATER LEVEL 253 ft. below land surface measured on mo/day/yr 6-5-12 pump test data: Well water was ft. after hours pumping gpm								
		Pump	test data: Well water	was	ft.	after	hours pum	ping gpm	
NW	NE	EST. YIELD	gpm. Well water	was	tt.	atter	hours pun	iping gpiii	
W Bore Hole Diameter 30 in to 500 ft., and in to								. Il.	
<del></del>				Public wat	er supply				
SW	Domestic								
SW SE									
<u> </u>		Was a chemical	/bacteriological sample	submitted to	Deparu	nem?	162 110		
1	S -1 mile		/day/yr sample was sub						
,	, ,	. 1	nfected?  Yes		1 1 1 1 1 1 1 1 1				
5 TYPE	OF CASING	USED: 🗹 Stee	I PVC C	Other					
CASING IOINTS:   Glued   Clamped   Welded     Threaded									
Cooling diameter 16 in to 275 ft Diameter in to									
Casing	Casing height above land surface 12 in., Weight 42.05 lbs./ft., Wall thickness or gauge No. 42.05								
TYPE OF SCREEN OR PERFORATION MATERIAL:									
Steel Stainless Steel PVC Other (Specify)									
Brass Galvanized Steel None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:  Continuous slot  Mill slot  Gauze wrapped  Torch cut  Drilled holes  None (open hole)									
Lawrened shutter									
SCREEN-PERFORATED INTERVALS: From 275 ft. to 415 ft., From 435 ft. to 500									
From ft to ft From tt. to It.									
GRAVEL PACK INTERVALS: From 20 ft. to 200 ft. From 260 ft. to 300 ft. to									
From ft to ft From tt. to									
COPOLIT MATERIAL. Neet coment V Cement grout Rentonite Ofther									
Grout Intervals: From 0 ft. to 20 ft., From 200 ft. to 260 ft., From ft. to									
	the nearest sou	rce of possible con-	tamination:						
	Septic tank	Lateral li	ines 🔲 Pit privy					ther (specify below)	
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well									
		er lines					gas wen		
in the same of the			OLG LOG			TITUO I	OG (cont.) or PI	UGGING INTERVALS	
FROM	TO	LITHOLO	GIC LOG	FROM	ТО	LITIO. I	CO (COIII.) OI FL	O O OTTIO TITITIO I	
0		PLAIN CASING	CODEEL					er	
275		JOHNSON AGRI		<del>                                     </del>					
335		MILL SLOT PERF		-	<u> </u>	CEE ATT	ACHEDIOC	The second secon	
355		JOHNSON AGRI	SCREEN			SEE ALI	ACHED LOG	· · · · · · · · · · · · · · · · · · ·	
415	<del> </del>	PLAIN CASING	CODERA				The state of the s	Andrew Committee	
435		JOHNSON AGRI			·		Autor Comment		
495	500 16"	MILL SLOT PERF	•		·	-	· · · · · · · · · · · · · · · · · · ·	Marie Company	
			and the second of the second o			<u> </u>	and the same of th		
				-			. i.a.	<u></u>	
				DAT. FD1 '	ham 11		tmustad I range	structed or I plugged	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was \( \bigsize \) constructed, \( \bigsize \) reconstructed, or \( \bigsize \) plugged									
under my jurisdiction and was completed on (mo/day/year) .6-5-12									
Kansas Water Well Contractor's License No. 208. This Water Well Record was completed on (mo/day/year)									
under the business name of MINTER-WILSON DRILLING CO., INC. by (signature) Moral Rellery									
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Therefore 185-296-5524 with 17 strength and retain one for your records.									
http://www.kdheks.gov/waterwell/index.html.									
KSA 82a-1212 Check: White Copy, Deluc Copy, Pink Copy									

24,380

## The Irrigation and Domestic Water Systems Professionals WINTER-WILSON DRILLING CO Water Systems Complete Installation and Populing

Irrigation and Repairing

## INCORPORATED

GARDEN CITY, KANSAS 67846 P.O. Box A

NAME

FLETCHER RANCH - CIRCLE # 42

COUNTY

KEARNY

DATE

3-5-12

LOCATION:

SW 1/4 32-25-35 - SOUTHEAST PART OF CIRCLE

STATIC WATER LEVEL -

## TEST#3

0' TO 9' - FINE SAND

9' TO 14' - BROWN CLAY

14' TO 100' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

WITH LAYERS OF BROWN SANDY CLAY

100' TO 160' - FINE TO MEDIUM SAND & GRAVEL

WITH LAYERS OF BROWN SANDY CLAY

160' TO 175' - BROWN SANDY CLAY

WITH STRIPS OF SAND & GRAVEL

175' TO 195' - BLUE CLAY

195' TO 203' - BROWN SANDY CLAY

203' TO 212' - FINE TO MEDIUM SAND & GRAVEL

WITH LAYERS OF BROWN SANDY CLAY

212' TO 240' - BROWN SANDY CLAY

240' TO 254' - FINE TO MEDIUM SAND & GRAVEL

254' TO 262' - BROWN SANDY CLAY

262' TO 280' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN SANDY CLAY - 20%

280' TO 287' - BROWN SANDY CLAY

287' TO 289' - FINE TO MEDIUM SAND & GRAVEL

289' TO 301' - BROWN SANDY CLAY

301' TO 318' - FINE TO MEDIUM SAND

WITH LAYERS OF BROWN SANDY CLAY - 30%

318' TO 373' - BROWN SANDY CLAY

WITH STRIPS OF WHITE ROCK

373' TO 387' - FINE TO MEDIUM SAND

WITH LAYERS OF BROWN SANDY CLAY - 15%

387' TO 400' - BROWN, YELLOW & WHITE CLAY

WITH 20% BROWN ROCK

400' TO 403' - LOOSE BROWN ROCK

403' TO 415' - BROWN, YELLOW & WHITE CLAY

WITH 20% BROWN ROCK

415' TO 446' - SHALE & WHITE SANDY CLAY MIXED

446' TO 453' - SHALE WITH STRIPS OF FINE SAND - 30%

453' TO 460' - SHALE

460' TO 465' - SHALE WITH STRIPS OF FINE SAND

465' TO 473' - FINE SAND & BROWN ROCK

473' TO 481' - SHALE

481' TO 485' - ? SAND STONE - LOST CIRCULATION