

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Kearny		NE $\frac{1}{4}$ SW $\frac{1}{4}$ SW $\frac{1}{4}$	10	T 25 S	R 36 E W

Distance and direction from nearest town or city street address of well if located within city?

South of Lakin 3 miles $\frac{1}{2}$ west $\frac{3}{4}$ South $\frac{1}{4}$ East South into

2 WATER WELL OWNER: #1-I Beymer	Murfin Drilling	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	Box 661	Application Number: T89-496
City, State, ZIP Code :	Colby, KS 67701	

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

NW	NE
SW	SE

DEPTH OF COMPLETED WELL: 220 ft. ELEVATION: 140 ft.

Depth(s) Groundwater Encountered 1. 80 ft. 2. 11-3-89 ft. 3. 85 ft.

WELL'S STATIC WATER LEVEL 80 ft. below land surface measured on mo/day/yr 11-3-89

Pump test data: Well water was 75 ft. after 2 hours pumping 85 gpm

Est. Yield 90 gpm Well water was 220 ft. after 9 hours pumping 85 gpm

Bore Hole Diameter 9 in. to 220 ft., and 2 in. to 220 ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	9 Dewatering
	7 Lawn and garden only	10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No ☒ No ☒ If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes ☒ No ☐

5 TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued ☒ Clamped ☐	
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded ☐	
<u>2 PVC</u>	4 ABS	7 Fiberglass		Threaded ☐	
Blank casing diameter <u>5</u> in. to <u>120</u> ft., Dia. in. to . ft., Dia. in. to . ft.					
Casing height above land surface <u>14</u> in., weight <u>200</u> lbs./ft. Wall thickness or gauge No. <u>0.265</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:			<u>7 PVC</u>	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify) ☐	
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:			5 Gauzed wrapped	<u>8 Saw cut</u>	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes		
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify) ☐		
SCREEN-PERFORATED INTERVALS:			From <u>120</u> ft. to <u>220</u> ft.,	From . ft. to . ft.,	
			From . ft. to . ft.,	From . ft. to . ft.,	
GRAVEL PACK INTERVALS:			From <u>70</u> ft. to <u>220</u> ft.,	From . ft. to . ft.,	
			From . ft. to . ft.,	From . ft. to . ft.,	

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other **Hole plug**
Grout Intervals: From 0 ft. to 20 ft., From _____ ft. to _____ ft., From _____ ft. to _____ ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) _____
13 Insecticide storage _____
Direction from well? **West** How many feet? **250**

[illegible]

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-3-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 142 This Water Well Record was completed on (mo/day/yr) 11-7-89 under the business name of T & W Water Well Service, Inc. by (signature) C. J. Wagner