


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Kearny	SE 1/4 NW 1/4 SW 1/4	22	T 25 S	R 36 EW

Distance and direction from nearest town or city street address of well if located within city?

4 3/4 miles South of Lakin KS

2 WATER WELL OWNER: Lee 1-I	Plains Petroleum	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	Murfin Drilling	Application Number: T88-53
City, State, ZIP Code :	Box 661 Colby, KS	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL. 275 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 155 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 120 ft. below land surface measured on mo/day/yr 2-3-88
	Pump test data: Well water was 115 ft. after 2 hours pumping 60 gpm
	Est. Yield 65 gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 9 in. to 275 ft., and in. to ft.
	WELL WATER TO BE USED AS:
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
	Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 5 in. to 0-195 ft., Dia			11 Other (specify)
Casing height above land surface 14 in., weight 200 lbs./ft. Wall thickness or gauge No. 0-265			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC		
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 120 ft. to 275 ft.		
	From ft. to ft.		
GRAVEL PACK INTERVALS:	From 115 ft. to 275 ft.		
	From ft. to ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 20 ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? East			13 Insecticide storage	
			How many feet? 200	

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	120	Fine sand and / blue clay			
120	140	Blue clay			
140	160	Blue clay			
160	180	Blue clay			
180	200	Fine sand and clay			
200	220	Coarse sand and clay			
220	240	Medium sand and blue clay			
240	260	Medium sand and blue clay			
260	275	Medium sand and blue clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-3-88 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 142 This Water Well Record was completed on (mo/day/yr) 2-5-88
under the business name of T & W Water Well Service, Inc. by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.