USE TYPEWRITER OR BALL POINT PEN-PRESS TRAILY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| | County | Fraction | | Section number | | Township number | Range number | | |
|--|--|---------------------------------------|-----------------|---|--|---|------------------------------------|-------------|--|
| . Location of well: | KEARNY | NW 1/4 SE 1/4 SE | 1/4 | | 24 | т 25 | s R . 36 | ∮ /w | |
| Distance and directly South | ection from nearest town or city: 4 | | 3. Own | er of well | . M | t 25 inter -Wilson I ox A | Drilling Co. | | |
| reet address of we | | | | arden City, Ks. 67846 | | | | | |
| 4. Locate with "X" in section below: Sketch map: | | | | | | 6. Bore hole dia. 26 in. Completion date 1-26-76 Well depth 360 ft. | | | |
| I I I | | | | | | 7 Cable tool Rotar Hollow rod Jette | | se rotary | |
| NW | | | | 8. Use: Domestic Public supply Industry X Irrigation Air conditioning Stock | | | | | |
| W 1 | | | | Lawn | Oil field water Oth | er | | | |
| sw | | | | 9. Casing: MaterialST | Surface12 | in. | | | |
| | S Aile ———————————————————————————————————— | | | | | PVC PVC | Weight 36,87 | hes or | |
| 5. Type and color of material | | | | From | То | Dia in. to ft. de | pth gage No. 2/9/ | nac | |
| | | | | | | 10. Screen, Manufacturer Johnson I | | _ | |
| | | | | | | Slot/gauze 100 | Length | | |
| | | · · · · · · · · · · · · · · · · · · · | | † | P | Set between 320 Prf . 120-210 ft. | and 300-320, 3L | | |
| | | | | | | Gravel pack?Size | | /day/yr. | |
| <u> </u> | | | | <u> </u> | ······································ | 72 ft. below land s | urface Date 2_8_7 | 6 | |
| | | | | | | 96 ft. after 3 | hrs. pumping 1400 | | |
| | | | | | | ft. after Estimated maximum yield _ | | g.p.m. | |
| | | | | | | 13. Water sample submitted Yes X No | : mo./ Date | /day/yr. | |
| | | | | | | 14. Well head completion: Pitless adapter | 12 Inches above g | rade | |
| | | | | - | | 15. Well grouted PCS With: Neat cement | - | | |
| | | | | ļ | | Depth: From ft. t | 1() | | |
| | | · | | | | 16. Nearest source of possi | | N/A | |
| | | | | - | | Well disinfected upon comp | ALAS ALI | No | |
| | | | | - | | Manufacturer's name Model number 12JH | | <u> </u> | |
| | | | | ļ | | Length of drop pipe | 60 ft. capacity 100 | .m. φ. | |
| | | | | | | Submersible | X Turbine | | |
| | (Use a second | sheet if needed) | 15 TE | 17181 | 203 | Jet Centrifugal | Reciprod | caring | |
| 18. Elevation: | 19. Remarks: | | 2 . | JAN ∘ | | Tom. 703 | my jurisdiction and this | report | |
| Topography: | | E | RE | CEN | o 18 Ment | in the best of my kn | owledge and belief. rilling 208 | | |
| Hill Slope | | 186 | SURV | S GEOL) EY - Gro er Sooti- | OGICAL | Brancess Barred Box | | Nise Nises | |
| Stope Upland Valley | | Je. | o Wati €o | er Section | in Te | Authorized r | presentative | 16 | |
| | Lue and pink copies to the Departmen | A of Harlth and Environment | V () | 1523 | 16 17 | | Form WW | | |

Phone 276-8269 • P.O. Box 493 • GARDEN CITY, KANSAS 67846

Minter- Wison

CHUCK JAEGER Kearny County 11-20-75

Location: SE 24-25-36
30 feet East of Pivot
Pivot 40

Static Water Level - 801

| 0 | 1 | Top Soil |
|---------------------|------|--|
| 1 | 13 | Fine Sand |
| 13 | 65 | Med. Coarse Gravel (Loose) |
| 65 | | Brown Sandy Clay |
| 1 13 65 91 | | Med. Sand & Gravel. |
| 155 | Dis. | Blue Clay |
| 171 | | Fine to Med. Sand & Gravel (Loose) |
| 214 | | Brown Sandy Clay |
| 234 | 2lah | Fine to Med. Sand & Gravel. |
| 214 | 306 | Brown Sandy Clay |
| 306 | 356 | Fine to Med. Sand & Gravel. |
| 306 356 | 360 | Fine to Med. Sand & Gravel mixed with Brown |
| | | Reck |
| 360 | 382 | Brown Yellow Clay mixed With Brown Rock (Hard) |
| 382 | 395 | Shale |

T.D. 360'