•			WATI	ER WELL RECORD	Form WWC-5	KSA 82a-			
1 LOCATION			Fraction	3.77	NTC:	tion Number	Township Number 25	200	_
	Kearny		SW 1	$_4$ NE $_{1/4}$ address of well if loc	NE 1/4	26	т 25	S R 30	E/W)
					-	Mila Fact	- 1 205 E4 N	forth & Q50 Ft W	ost
					SOUTH, I	TIC ESS!	υ, 4,200 Ft. IV	orth & 950 Ft. W	CSL
2 WATER W		A 10 A 10	I Leasing, . O. Box 89				Decard of Acris	ultura Division of Water De	
RR#, St. Add				, Kansas 6784	6		•	ulture, Division of Water Re mber: 19,155	sources
City, State, ZI						4. E. E. (A)		10, 100	
AN "X" IN	SECTION	BOX:							
	, }							ft. 3	
1	i	122						urs pumping	
	NW	NEX	I .					ours pumping	
<u>'</u>	! !	!							
* w	-: +	E	1					in. to	· · · · · · · · · ·
<u>-</u>	- 1	1 1	1 Domestic	TO BE USED AS: 3 Feedlot	6 Oil field water	r supply	8 Air conditioning	12 Other (Specify below	
	SW	SE	2 rrigation		7 Laws and c	er supply	O Monitoring well		~ ''
	!	: 1						; If yes, mo/day/yr sample w	
<u>t</u>			mitted	/bacteriological samp	ne submitted to De		ter Well Disinfected?		. 1
5 TYPE OF	BLANK C	ASING USED:	Timted	5 Wrought iron	8 Concre			: Glued Clamped .	
Steel		3 RMP (S	(R)	6 Asbestos-Ceme				Welded X	
2 PVC		4 ABS	,	7 Fiberglass		` '	,	Threaded	
	diameter		in. to 230	-				in. to	
								auge No	
		R PERFORATIO		,oigin	7 PV		10 Asbesto		
1)Steel		3 Stainles		5 Fiberglass		IP (SR)		specify)	
2 Brass		4 Galvani		6 Concrete tile	9 AB		•	sed (open hole)	
		RATION OPENIN			auzed wrapped		8 Saw cut	11 None (open ho	ole)
	nuous slo		/ill slot		ire wrapped		9 Drilled holes	, , , , , , , , , , , , , , , , , , ,	,
	ered shutte		Key punched		orch cut				
		D INTERVALS:		.230 ft. to	360	ft., Fror		ft. to	
								ft. to	
GRA	AVEL PAG	CK INTERVALS						ft. to	
			From	ft. to					
6 GROUT M	IATERIAL	: 1 Neat	cement	2 Cement grout	3 Bento	nite 4	Other		
Grout Interval	ls: Fron	n				to	ft., From	<u> ft</u> . to	ft.
What is the n	nearest so	urce of possible	contamination:			10 Livest	tock pens	14 Abandoned water well	11
1 Septic tank 4 Lateral line			ral lines	7 Pit privy		11 Fuels	11 Fuel storage 15 Oil well/Gas well		
2 Sewe	r lines	5 Cess		8 Sewage lagoon		12 Fertilizer storage 16 Other (specify below)			
3 Water	rtight sew	er lines 6 Seep	page pit	9 Feedyard	1	13 Insect	ticide storage		
Direction from	n well?	Souther	ast			How mar		. South & 30 Ft.	East
FROM	то		LITHOLOGIC	LOG	FROM	то	PLUG	GING INTERVALS	
		See a	ttached Log	Z					
								, , , , , , , , , , , , , , , , , , ,	
7 CONTRAC	CTOR'S	R LANDOWNE	R'S CERTIFICAT	ΓΙΟΝ: This water we	ll was (1) constru	cted, (2) reco	nstructed, or (3) plugg	ed under my jurisdiction a	nd was
completed on			4-18-94					my knowledge and belief.	
				This Wate	r Well Record wa		on (mo/day/yr)		
				rilling Co.,		by (signat	A		
	010. 11 1	newriter or ball point	pen. PLEASE PRESS	FIRMLY and PRINT clearly	. Please fill in blanks,	underline or circle	the correct answers. Send to	op three copies to Kansas Departn	nent .
INSTRUCTION	UNS: Use ty	bottittot of bott					WNER and retain one for you		

MINTER-WILSON DRILLING CO. und Domestic Water Systems

INCORPORATED

Phone 276-8269 P.O. Box A . GARDEN CITY, KANSAS 67846

> A. I. Leasing Kearny County 2-18-94

NE1 26-25-36 Location:

> 1½ Miles North of Fletcher Shop on Lakin Lane, 1 Mile East, 1 Mile North & 1 Mile

West (299' N of Well)

Static Water Level -

Test #2

0' to 1' - Top soil

1' to 11' - Brown sandy clay 11' to 37' - Medium to coarse gravel

37' to 54' - Coarse gravel

54' to 63' - Brown clay

63' to 82' - Coarse gravel

82' to 109' - Brown clay

109' to 161' - Blue clay

161' to 199' - Fine to medium sand and gravel

199' to 215' - Brown sandy clay

215' to 232' - Brown clay with gravel streaks 232' to 238' - Fine to medium sand and gravel-10% clay

238' to 252' - Fine to medium sand and gravel-loose

252' to 277' - Brown sandy clay

277' to 294' - Fine to medium sand and gravel-10% clay

294' to 310' - Fine sand

310' to 323' - Brown sandy clay

323' to 334' - Brown clay

334' to 351' - Fine to medium sand and gravel -

15% clay - tight

351' to 364' - Brown clay

364' to 378' - Brown clay brown rock mixed - tight

378' to 385' - Brown clay

385' to 404' - Brown and yellow clay

404' to 410' - Shale - pull down