

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Kearney		SE 1/4 NW 1/4 NW 1/4	33	T 25 S	R 36 E/W
Distance and direction from nearest town or city street address of well if located within city? 6 S 1/4 E of Lakin, KS					
2 WATER WELL OWNER: Lee S-33 Zenith Drilling					
RR#, St. Address, Box #: Suite 505 4th Financial Center					
City, State, ZIP Code: Wichita, KS 67202					
Board of Agriculture, Division of Water Resources Application Number: T 85-7					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 240 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 140 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 100 ft. below land surface measured on mo/day/yr 1/10/85			
		Pump test data: Well water was 135 ft. after 2 hours pumping 55 gpm			
		Est. Yield 70 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 9 in. to 240 ft., and in. to ft.			
WELL WATER TO BE USED AS:					
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well 12 Other (Specify below)					
Was a chemical/bacteriological sample submitted to Department? Yes.....No X; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes X No					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 5 in. to 55 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 14 in., weight 200 lbs./ft. Wall thickness or gauge No. 0.265					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 100 ft. to 240 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 90 ft. to 240 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? SW How many feet? 280					
FROM TO LITHOLOGIC LOG			FROM TO LITHOLOGIC LOG		
0	100	Overburden			
100	120	Med Sand + clay			
120	200	Coarse Sand			
200	220	Coarse Sand + clay			
220	240	Coarse Sand + Gravel			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1/10/85 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 142 This Water Well Record was completed on (mo/day/yr) 1/14/85					
under the business name of T+W Water Well Service Inc by (signature) <i>[Signature]</i>					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4