WATER WELL I	RECORD	Form WWC-	5	Division of Wate	er Resources; App. No.	19,156
1 LOCATION OF WATER WELL:		Fraction		Section Number	Township Number	Range Number
		SW 1/4 SW 1/4 S		36	T 25 S	R 36 EW
Distance and direction from nearest town or city street address of well if				Global Positioning Systems (decimal degrees, min. of 4 digits)		
located within city? Lakin, 1 M. S., 1/8th M. E., 6 M. S.				Latitude:		
2 M. E., 2,555 Ft. west & 120 ft. north				Longitude:		
2 WATER WELL OWNER: A I Leasing				Elevation:		
RR#, St. Address, Box # : PO Box 897 City, State, ZIP Code : Garden City, KS 67846				Datum:		
	Ourden o	ity, KS 67846		Data Collection		
3 LOCATE WELI	2'S 4 DEPTH OF COM	PLETED WELL	410	ft.		
LOCATION						
WITH AN "X" IN Depth(s) Groundwater Encountered (1)						
SECTION BOX: WELL'S STATIC WATER LEVEL198ft. below land surface measured on mo/day/yr5-:30-:08 Pump test data: Well water was						
		n: Well water was				
	WELL WATER TO E					
WELL WATER TO BE USED AS: 5 Public water supply WELL WATER TO BE USED AS: 5 Public water supply Domestic 3 Feedlot 6 Oil field water supply Domestic 3 Feedlot 6 Oil field water supply Domestic 3 Feedlot 6 Oil field water supply WELL WATER TO BE USED AS: 5 Public water supply Domestic 3 Feedlot 6 Oil field water supply WELL WATER TO BE USED AS: 5 Public water supply Domestic 3 Feedlot 6 Oil field water supply WELL WATER TO BE USED AS: 5 Public water supply WELL WAT						
"		lustrial 7 Domesti				·····
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs						
Sample was submitted						
S						
5 TYPE OF CASIN	IG USED: 5 Wrought	Iron 8 Conc	rete tile	CASIN	G JOINTS: Glued	Clamped
(1)Steel 3	RMP (SR) 6 Asbestos	-Cement 9 Other	(specify	below)	Welded	XX
2 PVC 4	ABS 7 Fiberglas	s		*******	Threaded	1
2 PVC 4 ABS 7 Fiberglass Threaded Blank casing diameter 16 in. to 215 ft., Diameter in. to ft., Diameter in. to ft.						
Casing height above land surface						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1) Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify)						
2 Brass 4 Galvanized Steal 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:						
1 Continuous slot 2 Mill slot 5 Gauzad veranned 7 Torch out 0 Drilled holes 11 None (onen hole)						
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)						
SCREEN-PERFORATED INTERVALS: From. 215 ft. to 410 ft., From ft. to ft.						
From ft. to ft., From ft. to ft.						
GRAVEL PACK INTERVALS: From						
	From	ft. to .		ft., From	ft. to	ft.
C CDOLLE MATERI	NAT . 1 N	C		4.04.		· · · · · · · · · · · · · · · · · · ·
6 GROUT MATER Grout Intervals:	From	Cement grout 3 Ber 20 ft., From	ntonite 140	4 Otner	 Р. Енона	A + A
	ource of possible contamina		. .	11. 10	u., From	11. 1011.
1 Septic tank	4 Lateral lines		0 Livesto	ick nens 13 In	secticide Storage	16 Other (specify
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel s						
3 Watertight se		~ ~			oil well/gas well	•
	0 200pmg0 pm			_	·····	N/A
FROM TO	LITHOLOGIC		FROM		PLUGGING INT	
	•					
	See attached 1	.og				
						•
				1 1		
			ļ	-		
			<u> </u>			
# CONTRIB A CONCE	CODIATION CONTRACTOR		<u> </u>		1 (2)	. 1 (2) 1 .
	S OR LANDOWNER'S C					
	n and was completed on (mo					
	Contractor's License No ame of Minter-Wilson			ord was complete (signature)		u
	typewriter or ball point pen. <u>PLE</u>					correct answers. Send ton
three copies to Kansas De	epartment of Health and Environme	ent, Bureau of Water, Geolo	gy Section,	1000 SW Jackson St.	Suite 420, Topeka, Kansa	s 66612-1367. Telephone
785-296-5522. Send	one to WATER WELL OWN	NER and retain one fo	r your re	cords. Fee of \$5	.00 for each constructed	ed well. Visit us at
http://www.kdheks.gov/w	aterwell/index.html.					

MINTER-WILSON DRILLING CO. Water Systems Complete Installation

Irrigation and Domestic and Repairing

INCORPORATED

Phone 276-8269 P.O. Box A **GARDEN CITY, KANSAS 67846**

NAME

BRENT TOKOI

COUNTY DATE

KEARNY 1-30-08

LOCATION:

SE 1/4 36-25-36 - SOUTH ON LAKIN LANE 6 MILES,

1-1/2 MILES EAST, 87 FT. NORTH & 67 FT. EAST

STATIC WATER LEVEL - 175 FT.

TEST #13

0' TO 1' - TOP SOIL

1' TO 3' - FINE SAND - LOOSE

3' TO 11' - BROWN CLAY

11' TO 18' - FINE TO MEDIUM SAND & GRAVEL

18' TO 21' - BROWN CLAY

21' TO 52' - FINE TO MEDIUM SAND & GRAVEL

52' TO 104' - MEDIUM COARSE GRAVEL

104' TO 112' - GRAY CLAY

112' TO 122' - MEDIUM COARSE GRAVEL

122' TO 129' - GRAY CLAY

129' TO 145' - FINE TO MEDIUM SAND & GRAVEL

145' TO 154' - BROWN CLAY

154' TO 163' - FINE TO MEDIUM SAND & GRAVEL

163' TO 175' - GRAY CLAY

175' TO 186' - BLUE CLAY

186' TO 190' - FINE TO MEDIUM SAND & GRAVEL

190' TO 209' - BROWN SANDY CLAY

209' TO 220' - FINE TO MEDIUM SAND & GRAVEL

220' TO 227' - BROWN SANDY CLAY

227' TO 235' - FINE TO MEDIUM SAND

235' TO 273' - BROWN SANDY CLAY

273' TO 289' - BROWN CLAY

289' TO 296' - BROWN CLAY - CEMENTED SAND STRIPS

296' TO 305' - BROWN CLAY

305' TO 311' - BROWN CLAY - SMALL FINE SAND STRIPS

311' TO 338' - BROWN CLAY

338' TO 345' - FINE TO MEDIUM SAND & GRAVEL-BROWN ROCK MIXED

345' TO 351' - BROWN CLAY

351' TO 358' - BROWN ROCK WITH BROWN CLAY - 50-50

358' TO 382' - BROWN YELLOW CLAY MIXED

382' TO 384' - BROWN ROCK - LOOSE

384' TO 392' - BROWN YELLOW CLAY - SMALL BROWN ROCK STRIPS

392' TO 440' - GRAY SHALE - HARD PULL DOWN 200