WATER WELL RECORD	Form WWC-5	Division of Water	Resources App. No	0. 19,154	
1 LOCATION OF WATER WELL: County: KEARNY	Fraction  4 SE 4 NW 4 NE 4	Section Number 35	Township No. T 25 S	Range Number R 36  □E  ☑W	
Street/Rural Address of Well Location;		Global Positioning	System (GPS) in	formation:	
from nearest town or intersection: If at owner's address, check here . Latitude:					
S SIDE OF LAKIN-1 M S, 1/4 M E TO LAKIN LANE, 6 M S, 1 M E, 4,005 FT. N. & 1,615 FT. W.		Longitude → 101 . 23593 (in decimal degrees)   Elevation:     Datum: □ WGS 84, □ NAD 83, ▼ NAD 27			
2 WATER WELL OWNER: TFT ALFALFA FARMS		Datum: WGS 84, NAD 83, K NAD 27 Collection Method:			
	GPS unit (Make/Model:Garmin .62ST)				
RR#, Street Address, Box #: 1320 N COUNTY ROAD 11 City, State, ZIP Code : LEOTI, KANSAS 67861		☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
	10110A0 07001	Est. Accuracy: <			
3 LOCATE WELL	COMPLETED WELL 430	Δ		·	
			A (	2\ A	
N WELL'S STAT	[ = 1 = (-) = 1 = 1 = 1 = 1 = 1 = 1 = 1 = 1 = 1 =				
Pumr	Pump test data: Well water wasft. after hours pumping				
NW NE EST. YIELDgpm. Well water wasft. after hours pumpinggpm					
w					
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well					
SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)					
☐ ☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No  If yes, mo/day/yr sample was submitted					
Water west distributed.					
5 TYPE OF CASING USED: Steel PVC Other Other					
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter					
Casing height above land surface					
TYPE OF SCREEN OR PERFORATION	MATERIAL:	ios./ic., wan tiller	thess of gauge 14th	UTAP	
✓ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)					
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:  Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)					
☐ Continuous slot   ☑ Mill slot   ☐ Gauze wrapped   ☐ Torch cut   ☐ Drilled holes   ☐ None (open hole)   ☐ Louvered shutter   ☐ Key punched   ☑ Wire wrapped   ☐ Saw cut   ☐ Other (specify)					
SCREEN-PERFORATED INTERVALS: From260					
From					
GRAVEL PACK INTERVALS:	From20	ft., From . ?	50 ft. 1	to430 ft.	
From					
Grout Intervals: From	ent V Cement grout Benton	ite $\Box$ Other			
What is the nearest source of possible conta	amination:	1. 10 11.,	rrom	. п. юп.	
Septic tank					
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☑ Abandoned water well					
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well  Direction from well SOUTHEAST ☐ Distance from well .45', \$\&295', \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\					
FROM TO LITHOLOG				CODIO DITERVALO	
LITOLOG	GIC LOG FROM	TO LITHO. LO	G (cont.) or PLU	GGING INTERVALS	
			-		
SEE ATTACHED LOG	3		***************************************		
3==:::///					
				- <del> </del>	
			***		
7 CONTRACTORIS OR LANDOWS	DIG CURPTIES CARTON CT		. , , ,		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was   ☐ constructed, ☐ reconstructed, or ☐ plugged under my jurisdiction and was completed on (mo/day/year)8-16-12 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/year) .8-17-12					
under the business name of MINTER-WILSON DRILLING CO., INC. by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three conject					
(white, blue, pink) to Kansas Depar tment of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 666 12-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include <u>fee</u> of \$5.00 for each constructed well. Vi sit us at http://www.kdheks.gov/waterwell/index.html.					
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy					

## The Professionals MINTER-WILSON DRILLING CO. | Irrigation and Domestic Water Systems Complete Installation

and Repairing

INCORPORATED

Phone 620-276-8269 • P.O. Box A • GARDEN CITY, KANSAS 67846

NAME

**BRENT TOKOI - CIRCLE # T8** 

COUNTY

KEARNY

DATE

6-5-12

LOCATION:

NE 1/4 35-25-36 - LAKIN LANE & PARALLEL ROAD - 1/2 MILE NORTH,

1/4 MILE NORTH & 1/4 MILE EAST

- WEST OF PIVOT

STATIC WATER LEVEL - APPROX. 230 FT.

## TEST #1

0' TO 3' - SAND

3' TO 12' - BROWN SANDY CLAY

12' TO 105' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

105' TO 110' - BROWN CLAY

110' TO 145' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

145' TO 160' - BLUE CLAY

160' TO 197' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

197' TO 215' - BROWN SANDY CLAY

215' TO 232' - FINE TO MEDIUM SAND & GRAVEL

232' TO 255' - BROWN SANDY CLAY

255' TO 275' - BROWN CLAY

275' TO 283' - BROWN SANDY CLAY

WITH LAYERS OF SAND - 25%

283' TO 290' - FINE TO MEDIUM SAND & GRAVEL

290' TO 305' - BROWN CLAY

305' TO 323' - BROWN SANDY CLAY

323' TO 333' - FINE TO MEDIUM SAND

WITH STRIPS OF BROWN SANDY CLAY - 15%

333' TO 336' - BROWN SANDY CLAY

336' TO 355' - FINE TO MEDIUM SAND & SMALL GRAVEL

WITH STRIPS OF BROWN SANDY CLAY - 20%

355' TO 400' - BROWN SANDY CLAY

WITH STRIPS OF SAND - 10%

400' TO 405' - FINE TO MEDIUM SAND, GRAVEL & BROWN ROCK

WITH STRIPS OF BROWN SANDY CLAY - 20%

405' TO 411' - LOOSE BROWN ROCK

411' TO 418' - BROWN & YELLOW CLAY

WITH 20% BROWN ROCK

418' TO 425' - LOOSE BROWN ROCK

425' TO 435' - FINE TO MEDIUM SAND

435' TO 437' - HARD BLACK ROCK - 300 PULL DOWN

437' TO 451' - SAND STONE - TIGHT - 250 PULL DOWN