WATER WELL RECORD	Form W	WC-5	Division of Wate	r Resources App. No	14,288
1 LOCATION OF WATER WELL	Fraction	· •	Section Number	Township No.	Range Number
County: KEARNY			33	T 25 S	R 36
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here			Global Positioning System (GPS) information:  Latitude:		
S SIDE OF LAKIN-1 M S, 1/4 M E TO LAKIN LANE, 6 M S,			Longitude: (in decimal degrees)		
1 M W, 680 FT. NORTH & 2489 FT. WEST			Elevation:		
2 WATER WELL OWNER: JACK BOEGEL			Datum: ☐ WGS 84, ☐ NAD 83, ☐ NAD 27 Collection Method:		
RR#, Street Address, Box #: PO BOX 273			GPS unit (Make/Model:)		
City, State, ZIP Code : LAKIN. KS 67860			☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey  Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m		
3 LOCATE WELL WITH AN "X" IN SECTION BOX: N  Depth(s) Groundwater Encountered (1)					
Pump test data: Well water wasft. after hours pumping					
EST. YIELDgpm. Well water wasft. after hours pumping gpm					
W					
Demostic Decoder Doil field water graphy Developing Dother (Specify below)					
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No					
S If yes, mo/day/yr sample was submitted					
5 TYPE OF CASING USED:  Steel  PVC  Other					
CASING JOINTS: Glued Clamped Welded Threaded					
Casing diameter 16 in. to 220 ft., Diameter in. to ft., Diameter ft.					
Casing height above land surface 12					
✓ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)					
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:  Continuous slot  Mill slot  Gauze wrapped  Torch cut  Drilled holes  None (open hole)					
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)					
SCREEN-PERFORATED INTERVALS: From					
From					
From					
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other					
Grout Intervals: From 0					
Septic tank    Lateral lines    Pit privy    Livestock pens    Insecticide storage    Other (specify below)					
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well					
Direction from well					••••••
	LOGIC LOG	FROM			GGING INTERVALS
SEE ATTACHED L	.OG				
					· · · · · · · · · · · · · · · · · · ·
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was   ☐ constructed, ☐ reconstructed, or ☐ plugged under my jurisdiction and was completed on (mo/day/year)12-19-13 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No208 This Water Well Record was completed on (mo/day/year)12-20-13					
under the business name of MINTER-WILSON DRILLING CO., INC., by (signature) . Mara Killer					
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send one copy to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topel and St., Suite 420, Topel					
http://www.kdheks.gov/waterwell/index.html  JAN 1 4 2014					

## MINTER-WILSON DRILLING CO. Water Systems Complete Installation

Irrigation and Repairing

**INCORPORATED** 

Phone 620-276-8269 P.O. Box A • GARDEN CITY, KANSAS 67846

NAME

THREE BO'S, INC. - CIRCLE # 21

COUNTY

KEARNY

DATE

10-22-13

LOCATION:

SE 1/4 33-25-36 - FROM CUSTOMER'S SHOP - 1-3/4 MILES SOUTH

& 1/4 MILE EAST

- SOUTHWEST CORNER OF FIELD

1 TRACK IN

STATIC WATER LEVEL - APPROX. 180 FT.

## TEST#3

0' TO 1' - TOP SOIL

1' TO 17' - BROWN CLAY & BROWN SANDY CLAY

17' TO 147' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

147' TO 190' - BROWN CLAY

190' TO 215' - BROWN CLAY WITH GRAVEL STREAKS

215' TO 223' - BROWN CLAY

223' TO 235' - FINE TO MEDIUM SAND & GRAVEL

235' TO 290' - BROWN CLAY

290' TO 305' - FINE TO MEDIUM SAND & GRAVEL

305' TO 329' - BROWN SANDY CLAY

329' TO 336' - FINE TO MEDIUM SAND

336' TO 355' - BROWN SANDY CLAY

355' TO 377' - FINE TO MEDIUM SAND & GRAVEL

377' TO 385' - BROWN CLAY

385' TO 395' - BROWN YELLOW CLAY

395' TO 404' - YELLOW CLAY

404' TO 410' - SHALE

WHUS IN SE