

CORRECTED



WATER WELL RECORD Form WWC-5 1269661

Division of Water Resources App. No.


Well ID

Original Record Correction Change in Well Use

1 LOCATION OF WATER WELL: County: Kearny Fraction NW 1/4 NW 1/4 NE 1/4 Section Number 2 Township Number T 25 S Range Number R 36 E W

2 WELL OWNER: Last Name: Villanueva First: Juan Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): Hwy25 & River road .8 miles East sits on south side of Road.

3 LOCATE WELL WITH "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 255 ft. Depth(s) Groundwater Encountered: 1) 37 ft. 2) 37 ft. 3) 37 ft. or 4) Dry Well WELL'S STATIC WATER LEVEL: 37 ft. below land surface, measured on (mo-day-yr) 10/28/2015

5 Latitude: 37.91515 (decimal degrees) Longitude: 101.23963 (decimal degrees) Datum: WGS 84 NAD 83 NAD 27 Source for Latitude/Longitude: GPS (unit make/model: ) (WAAS enabled? Yes No) Land Survey Topographic Map Online Mapper:

6 Elevation: 3001 ft. Ground Level TOC Source: Land Survey GPS Topographic Map Other KOLAR

7 WELL WATER TO BE USED AS: 1. Domestic: Household Lawn & Garden Livestock Irrigation Feedlot Industrial 2. Public Water Supply: well ID 3. Dewatering: how many wells? 4. Aquifer Recharge: well ID 5. Monitoring: well ID 6. Environmental Remediation: well ID Air Sparge Soil Vapor Extraction Recovery Injection 7. Oil Field Water Supply: lease 8. Test Hole: well ID Cased Uncased Geotechnical 9. Geothermal: how many bores? a) Closed Loop Horizontal Vertical b) Open Loop Surface Discharge Inj. of Water 10. Other (specify):

Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted: Water well disinfected? Yes No

8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 5 in. to 255 ft. Diameter 14 in. to 110 ft. Diameter 14 in. to 255 ft. Casing height above land surface 14 in. Weight lbs./ft. Wall thickness or gauge No. SDR17

TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel Fiberglass PVC Other (Specify) Brass Galvanized Steel Concrete tile None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify) Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole) SCREEN-PERFORATED INTERVALS: From 215 ft. to 255 ft. From 110 ft. to 255 ft. GRAVEL PACK INTERVALS: From 24 ft. to 95 ft. From 110 ft. to 255 ft.

9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From 4 ft. to 24 ft. From 95 ft. to 110 ft. Nearest source of possible contamination: Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Other (Specify) Direction from well? west Distance from well? 300 ft.

Table with columns: 10 FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHO. LOG (cont.) or PLUGGING INTERVALS. Rows: 0-20 (fine sand/clay/coarse sand), 20-60 (sand/gravel/coarse sand), 60-80 (sand), 80-100 (sand/med. gravel/streak of clay), 100-120 (clay), 120-140 (streaks of fine sand/med sand/ clay), 140-160 (sand with streaks clay), 160-180 (sand/ gravel with streaks of clay), 180-240 (sand/gravel/coarse-med sand/clay). Notes: Notes:

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year) 10/27/2015 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 888 This Water Well Record was completed on (mo-day-year) 10/31/2015 under the business name of Steve's Drilling