

1 LOCATION OF WATER WELL: County: Kearny		Fraction SE 1/4 SE 1/4 SW 1/4		Section Number 8	Township Number T 25 S	Range Number R 37 E W
Distance and direction from nearest town or city street address of well if located within city? 7 1/2 west 4 south of Wxxxxx Lakin, Kansas						
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Carl Schmitt P. O. Box 173 Lakin, Kansas 67860 Board of Agriculture, Division of Water Resources Application Number:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 14.7 ft. ELEVATION: slope Depth(s) Groundwater Encountered 1. 4.0 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 4.0 ft. below land surface measured on mo/day/yr 9-21-94 Pump test data: Well water was Not installed ft. after hours pumping Est. Yield Not installed gpm. Well water was Not installed gpm Bore Hole Diameter 9 7/8 in. to 14.7 ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No				
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 5 in. to 10.7 ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface 18 in. weight schedule 200 lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 3 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 10.7 ft. to 14.7 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 2.0 ft. to 14.7 ft. From ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 2.0 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? East How many feet? 550						
FROM TO LITHOLOGIC LOG			FROM TO PLUGGING INTERVALS			
0	2	Surface				
2	15	Brown clay				
15	19	Coarse sand				
19	40	Blue shale				
40	120	Gray shale				
120	135	Gray shale w/sandstone				
135	145	Sandstone (loose)				
145	150	Blue shale				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/21/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 164 This Water Well Record was completed on (mo/day/yr) 10-21-94 under the business name of Houck Bros. Drlg. Co. by (signature) M. Beard						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.						