			WATE	R WELL RECORD	Form WWC-5	KSA 82a	1-1212		
1 LOCATI	ON OF WA	TER WELL:	Fraction			tion Number	Township Number	Range Number	
County: Kearny SW 1/4 NE 1/4 SW 1/4 25 T 25 S Distance and direction from nearest town or city street address of well if located within city?							<u> R 37 E(W) </u>		
				2½ West 4 South					
_		/NER: #1-I	Johnson	H-30 Dri		10			
	Address, Bo	x # :		251 N. Wa			_	Division of Water Resources	
	, ZIP Code	<u>:</u>	1 1	Wichita,			Application Number:		
3 LOCATE	E WELL'S L IN SECTIO	OCATION WITH					TION:		
^IV ^	IN SECTIO	7 50%.					2 ft. :		
7	. !	!	WELL'S STATIC	WATER LEVEL	. 40 ft. b	elow land su	face measured on mo/day/yr	3-12-89	
	- NW	NE	Pum	p test data: Well wate	rwas3() ft. a	ifter $\dots 2 \dots \dots$ hours p	umping7.0 gpm	
1 [1		Est. Yield 8	30 gpm: Well wate	rwas	ft. a	ifter hours po	umping gpm	
≝ w L	i		Bore Hole Diam	eter	1.80	ft.,	and	n. to	
w F		1 1	WELL WATER	TO BE USED AS:	5 Public wate	r supply	8 Air conditioning 11	Injection well	
7	1,5%		1 Domestic	3 Feedlot	6 Oil field wa	ter supply	9 Dewatering 12	Other (Specify below)	
	- 2W	35	2 Irrigation	4 Industrial	7 Lawn and g	arden only	10 Monitoring well		
1 1	i		Was a chemical	/bacteriological sample s	submitted to De	epartment? Y	es; If yes	s, mo/day/yr sample was sub-	
			mitted			Wa	ter Well Disinfected? Yes	X No	
5 TYPE C	OF BLANK (CASING USED:		5 Wrought iron	8 Concre	ete tile	CASING JOINTS: Glue	ed . X Clamped	
1 Ste	el	3 RMP (S	;R)	6 Asbestos-Cement		(specify below	w) Weld	ded	
2 PV	C	4 ABS	•	7 Fiberglass				aded	
		5	.in. to 1.00) ft Dia	in. to		ft., Dia	in. to ft.	
							ft. Wall thickness or gauge		
-	-	R PERFORATIO			7 PV		10 Asbestos-cem		
1 Ste		3 Stainles		5 Fiberglass		IP (SR))	
2 Bra		4 Galvania		6 Concrete tile	9 AB		12 None used (o		
		RATION OPENIN		5 Gauzed wrapped		-	8 Saw cut	11 None (open hole)	
1 Continuous slot 3 Mill slot 6 Wire wrapped							9 Drilled holes	(
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From									
From									
c	SRAVEL PA	CK INTERVALS:					m ft.		
•	21.0.1V CC 1.7.	OR HATELTANEO	From	ft. to		ft., Fro		to ft.	
6 GBOLIT	MATERIAL	: 1 Neat		2 Cement grout	3 Bento		Other		
							ft., From		
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines				7 Pit privy			10 Livestock pens 14 Abandoned water well 11 Fuel storage 15 Oil well/Gas well		
2 Sewer lines 5 Cess pool						12 Fertilizer storage 16 Other (specify below)			
		rer lines 6 Seep	•	8 Sewage lagoon9 Feedyard		13 Insecticide storage			
		Southwest		5 Feedyald			ny feet? 200		
Direction f	TO TO	Southwest	LITHOLOGIC	LOG	FROM	TO TO	PLUGGING	INTERVALS	
		Opposedning			1.101				
0	40_		en						
40	60	Gravel							
60_	80	Gravel	. 7 2!			 			
80	100		nd medium s						
100	120		nd medium s						
120	140		nd medium s						
140	160		nd medium s						
160	180	Gravel,	meclum sand	and sand ston	e				
					-			A	
			1.00		-				
41.74									
								- All Control of the	
						Ll			
							onstructed, or (3) plugged un		
							ord is true to the best of my kg	nowledge and belief. Kansas	
		•		This Water W				1-89	
				11 Service, Inc		-	iture) C. Wayen	eelle >	
							e the correct answers. Send top three		
							R WELL OWNER and retain one for y		