

WATER WELL RECORD Form WWC-5

Division of Water Resources App. No.

Well ID

Original Record Correction Change in Well Use

1 LOCATION OF WATER WELL: County: Hamilton Fraction S2 1/4 NE 1/4 NW 1/4 SE 1/4 Section Number 8 Township Number T 25 S Range Number R 42 E W

2 WELL OWNER: Last Name: Gouldner First: Doug Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here: Intersection of 25 Rd & F Rd 1 Mile South

3 LOCATE WELL WITH 'X' IN SECTION BOX: [Diagram] 4 DEPTH OF COMPLETED WELL: 560 ft. 5 Latitude: 37.890847 Longitude: 101.950482 6 Elevation: 3665 ft. Ground Level TOC

7 WELL WATER TO BE USED AS: 1. Domestic: Household Lawn & Garden Livestock Irrigation Feedlot Industrial 5. Public Water Supply 6. Dewatering 7. Aquifer Recharge 8. Monitoring 9. Environmental Remediation 10. Oil Field Water Supply 11. Test Hole 12. Geothermal 13. Other

Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted: Water well disinfected? Yes No

8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 5 in. to 560 ft. Diameter in. to ft. Casing height above land surface 18 in. Weight lbs./ft. Wall thickness or gauge No. SDR17 TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify) Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify) Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole) SCREEN-PERFORATED INTERVALS: From 400 ft. to 420 ft. From 560 ft. to 560 ft. GRAVEL PACK INTERVALS: From 50 ft. to 560 ft. From 560 ft. to 560 ft.

9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From 0 ft. to 50 ft. From 50 ft. to 50 ft. From 50 ft. to 50 ft. Nearest source of possible contamination: No potential source of contamination within 200 ft. Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Other (Specify) Direction from well? East Distance from well? 30 ft.

10 FROM TO LITHOLOGIC LOG FROM TO LITHO. LOG (cont.) or PLUGGING INTERVALS Attached Attached Attached Notes

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year) 09/20/2019 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 846 This Water Well Record was completed on (mo-day-year) 09/27/2019 under the business name of Nash Water Well Service, LLC

Form	WWC5
Contractor	Nash Water Well Service, LLC
Well Owner	Doug Gouldner
Doc ID	1472790

Litholgy

0	15	TOP SOIL FINE SAND TAN BROWN CLAY
15	20	TAN CLAY
20	40	FINE COARSE SAND WITH SMALL TO LARGE COBBLE AND CEMENTED SAND LAYERS
40	60	CEMENTED FINE MEDIUM SAND WITH ROCK LAYERS
60	65	YELLOW TAN CLAY
65	310	BLUE SHALE WITH ROCK LAYERS
310	320	BLUE SHALE GRAY SANDSTONE LAYERS & STREAKS
320	360	GRAY SANDSTONE WITH GRAY CLAY STREAKS
360	395	GRAY SANDSTONE & GRAY CLAY
395	430	GRAY SANDSTONE
430	440	BROWN GRAY CLAY WITH TAN SANDSTONE
440	460	GRAY CLAY
460	480	GRAY CLAY WITH GRAY SANDSTONE & ROCK LAYERS
480	500	GRAY SANDSTONE
500	520	GRAY SANDSTONE
520	530	GRAY SANDSTONE

Form	WWC5
Contractor	Nash Water Well Service, LLC
Well Owner	Doug Gouldner
Doc ID	1472790

Litholgy

530	540	BLUE SHALE
540	560	BLUE SHALED WITH THIN STREAKS OF SANDSTONE
560	570	BLUE SHALE