	ION OF WATER Y: 038 HANI			tion <b>N</b> 1/4 S					Section 21			l Town				-	Number W	
	nce and dire SYRACUSE, 7					stre	et addr	ess of	well if	loca	ted wi	thin ci	ty?					
RR#, S	WELL OWNER: St. Address, State, ZIP	Box # :		UTE		8-						icultur Number:			of W	ater Re	sources	
	E WELL'S LOC " IN SECTION		j				PLETED undwate		443 untered		VATION 1.			2.	0 ft	. 3	. 0	ft
1	i i		;	: \\EL	L'S ST	ATIC Pump	WATER L testda	.EVEL sta: W	280 ft. ell wate	belo r ₩as	w land 32	surfac 5 ft. a	e mea fter			/day/yr pumpin		
H	#   	NE	×	:   Est	imated	Yiel	d <b>60</b> 0	) gpm:	Well wat	er #a	\$	0 ft. a	fter	0	hours	pumpin	g <b>0</b>	gp
i W	 			E   Bor	e Hole	Diam	eter	2	4 in.	t o	443 f	t., and		in.	10	0 ft.		
е	¦ ; } \$₩	   \$E		¦ ₩EL	L WATE	R TO	BE USED	) AS: 0	2 IRRIGA	TION							;	}
1		   							cal samp s submit							l disin	fected?	Ye
Blank	OF BLANK CAS casing diam	eter	16 in	. to	443 ft	., D	ING JOI ia	in.	to 0	ft.,	Dia	i	n. to	(	) ft.			
Blank Casing TYPE (		eter ve land su PERFORATI	16 in rface ON MATER	. to 12 in. IAL: 01	,	., D ₩eig	ia ht 4	in.		ft., I thi	Dia ckness	i or gau	n. to ge No	25	) ft.			
Blank Casing TYPE ( SCREEN	casing diam g height abo DF SCREEN OR N OR PERFORA  N PERFORATED	eter ve land su PERFORATI TION OPENI  !NTERVALS	16 in rface ON MATER NGS ARE:	. to 12 in. IAL: 01 01	STEEL CONT.	., D weig SLOT	ia ht 4  to 44	in. 12 lbs/  10 ft.,	to 0	l thi  0 f	ckness  t. to	or gau	ge No  t.	25	) ft.			
Blank Casing TYPE ( SCREE	casing diam g height abo DF SCREEN OR N OR PERFORA	eter ve land su PERFORATI TION OPENI  !NTERVALS	16 in rface ON MATER NGS ARE:	. to 12 in. IAL: 01 01 From	STEEL CONT. 280 0	weig SLOT ft. ft.	ia ht 4 to 44 to 44	in. 12 lbs/ 10 ft., 0 ft., 13 ft.,	to Oft. Wal	Of 0 f	ckness t. to t. to t. to	or gau	ge No  t. t.	25	) ft.			
Blank Casing TYPE ( SCREEN SCREEN GROUT Grout What i	casing diam g height abo DF SCREEN OR N OR PERFORA  N PERFORATED	eter ve land su PERFORATI TION OPENI INTERVALS INTERVALS 03 BENTON From st source	16 in rface ON MATER NGS ARE: : : : : : : : : : : : : : : : : : :	. to 12 in. 1AL: 01 01 From From From 20	STEEL CONT. 280 0 20	weig SLOT ft. ft. ft. ft.	ia ht 4  to 44 to 44 to 0	in. 12 lbs/ 10 ft., 0 ft., 0 ft., 13 ft., 14. to	to Oft. Wal	Of 0 f	t. to t. to t. to	or gau	ge No t. t. t.	25 	·	· · · · · · · · · · · · · · · · · · ·	 	
Blank Casing TYPE ( SCREEN  SCREEN  GROUT Grout What i Direct	casing diam g height abo DF SCREEN OR N OR PERFORATED GRAVEL PACK MATERIAL Intervals: is the neare tion from we	eter ve land su PERFORATI TION OPENI INTERVALS INTERVALS O3 BENTON From st source II?	16 in rface ON MATER NGS ARE: : : : : : : : : : : : : : : : : : :	. to 12 in. 1AL: 01 From From From Control Contr	STEEL CONT. 280 0 20 0 ft., tamina	sLOT ft. ft. ft. ft. ft	ia ht 4  to 44 to 44 to 0	in. 12 lbs/ 10 ft., 0 ft., 0 ft., 13 ft., 14. to	to Oft. Wal	Of 0 f 0 f 0 f 0 f 0 f 0 f 0 f 0 f 0 f 0	t. to t. to t. to	or gau	ge No t. t. t.	25	t. Hov	v many ITERVAL		
Blank Casing TYPE ( SCREEN SCREEN GROUT Grout What i Direct FROM 0 160	casing diam g height abo DF SCREEN OR N OR PERFORATED GRAVEL PACK MATERIAL Intervals: is the neare tion from we 1 TO 1 160 1 202	eter ve land su PERFORATI TION OPENI INTERVALS INTERVALS  03 BENTON From st source        BRWN SA	16 in rface ON MATER NGS ARE: : : : : : : : : : : : : : : : : : :	to 12 in. 1AL: 01 01 From From From LITHOLO BROWN	STEEL CONT. 280 0 20 0 ft., tamina	sLOT ft. ft. ft. ft. ft	ia ht 4  to 44 to 44 to 0	in. 12 lbs/ 10 ft., 0 ft., 0 ft., 13 ft., 14. to	to Oft. Wal	Of 0 f 0 f 0 f 0 f 0 f 0 f 0 f 0 f 0 f 0	ckness  t. to t. to t. to t. to	or gau	ge No t. t. t.	25	t. Hov	·		
Blank Casing TYPE ( SCREEN SCREEN GROUT Grout What i Direct FROM 0 160 202 220	casing diam g height abo DF SCREEN OR N OR PERFORATED GRAVEL PACK  MATERIAL Intervals: is the neare tion from we 1 TO 1 160 1 202 1 220 1 280	eter ve land su PERFORATI TION OPENI INTERVALS INTERVALS  O3 BENTON From st source II? BRWN SA I SHALE SHALE S SANDSTO	16 in rface ON MATER NGS ARE: : : : : : : : : : : : : : : : : : :	. to 12 in. 1AL: 01  From From From From LITHOLO BROWN	STEEL CONT. 280 0 20 ft., tamina	sLOT ft. ft. ft. ft. ft	ia ht 4  to 44 to 44 to 0	in. 12 lbs/ 10 ft., 0 ft., 0 ft., 13 ft., 14. to	to Oft. Wal	Of 0 f 0 f 0 f 0 f 0 f 0 f 0 f 0 f 0 f 0	ckness  t. to t. to t. to t. to	or gau	ge No t. t. t.	25	t. Hov	·		
Blank Casing TYPE ( SCREEN SCREEN GROUT Grout What i Direct FROM 0 160 202 220 280 305	casing diam g height abo DF SCREEN OR N OR PERFORATED  GRAVEL PACK  MATERIAL Intervals: is the neare tion from we 1 160 202 220 280 305 395	eter ve land su PERFORATI TION OPENI INTERVALS INTERVALS O3 BENTON From st source II? BRWN SA SHALE SANDSTO SHALE SANDSTO	16 in rface ON MATER NGS ARE: : : : : : : : : : : : : : : : : : :	. to 12 in. 1AL: 01 From From From Con End End End End End End End End End En	STEEL CONT. 280 0 20 0 ft., tamina	sLOT ft. ft. ft. ft. ft	ia ht 4  to 44 to 44 to 0	in. 12 lbs/ 10 ft., 0 ft., 0 ft., 13 ft., 14. to	to Oft. Wal	Of 0 f 0 f 0 f 0 f 0 f 0 f 0 f 0 f 0 f 0	ckness  t. to t. to t. to t. to	or gau	ge No t. t. t.	25	t. Hov	·		
Blank Casing TYPE ( SCREEN SCREEN GROUT Grout What i Direct FROM 0 160 202 220 280	casing diam g height abo DF SCREEN OR N OR PERFORATED  GRAVEL PACK  MATERIAL Intervals: is the neare tion from we 1 160 202 220 280 305 395	eter ve land su PERFORATI TION OPENI INTERVALS INTERVALS O3 BENTON From st source II? BRWN SA SHALE SANDSTO SHALE SANDSTO	16 in rface ON MATER NGS ARE: : : : : : : : : : : : : : : : : : :	. to 12 in. 1AL: 01 From From From Con End End End End End End End End End En	STEEL CONT. 280 0 20 0 ft., tamina	sLOT ft. ft. ft. ft. ft	ia ht 4  to 44 to 44 to 0	in. 12 lbs/ 10 ft., 0 ft., 0 ft., 13 ft., 14. to	to Oft. Wal	Of 0 f 0 f 0 f 0 f 0 f 0 f 0 f 0 f 0 f 0	ckness  t. to t. to t. to t. to	or gau	ge No t. t. t.	25	t. Hov	·		

completed on (mo/day/year) 08/07/96 and this record is true to the best of my knowledge and belief. Kansas | Water Well Contractor's License No. 145 | This Water Well Record was completed on (mo/day/yr) 08/20/96 | under the business name of HENKLE DRILLING & SUPPLY | by (signature) Bury Reichmold