


1 LOCATION OF WATER WELL: County: <u>Sedgwick</u>		Fraction: <u>NE 1/4 NE 1/4 SE 1/4</u>		Section Number: <u>3</u>		Township Number: <u>T 26 S</u>		Range Number: <u>R 1 E</u>	
Distance and direction from nearest town or city street address of well if located within city? <u>7315 N. Hoover Valley Center</u>									
2 WATER WELL OWNER: <u>Roger Adams</u> RR#, St. Address, Box #: <u>1430 S. Washington</u> City, State, ZIP Code: <u>Wichita, KS 67211</u>						Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 			4 DEPTH OF COMPLETED WELL: <u>51</u> ft. ELEVATION: Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>14</u> ft. below land surface measured on mo/day/yr <u>1-3-97</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield <u>20</u> gpm; Well water was ft. after hours pumping gpm Bore Hole Diameter: <u>11</u> in. to <u>51</u> ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was sub- mitted Water Well Disinfected? Yes <u>X</u> No						
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped 2 <u>PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <u>5</u> in. to <u>40</u> ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface <u>12</u> in. weight <u>2.40</u> lbs./ft. Wall thickness or gauge No. <u>160 PSI</u>			TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) 7 Torch cut SCREEN-PERFORATED INTERVALS: From <u>40</u> ft. to <u>51</u> ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From <u>14</u> ft. to <u>51</u> ft. From ft. to ft. From ft. to ft. From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 <u>Cement grout</u> 3 Bentonite 4 Other Grout Intervals: From <u>3</u> ft. to <u>14</u> ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 <u>Sewage lagoon</u> 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? <u>Southwest</u> How many feet? <u>150</u>									
FROM TO LITHOLOGIC LOG			FROM TO PLUGGING INTERVALS						
0 14 clay									
14 30 fine sand									
30 31 clay									
31 51 gravel									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>1-3-97</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>318</u> This Water Well Record was completed on (mo/day/yr) <u>1-3-97</u> under the business name of <u>Weninger Drilling, Inc.</u> by (signature) <u>Michelle Becker</u>									