

1 LOCATION OF WATER WELL: Fraction NW 1/4 NE 1/4 SE 1/4 Section Number 3 Township Number T 26 S Range Number R 1 E NW

County: Sedgewick Distance and direction from nearest town or city street address of well if located within city: 611 Solar Valley Circle Valley Center

2 WATER WELL OWNER: Jones Building Board of Agriculture, Division of Water Resources

RR#, St. Address, Box #: 110494 SE 20 Application Number:

City, State, ZIP Code: Cheney, KS 67025

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36x36 section grid with an 'X' in the SE corner]

4 DEPTH OF COMPLETED WELL: 36 ft. ELEVATION: 2-11-99

Depth(s) Groundwater Encountered: 14 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL: 14 ft. below land surface measured on mo/day/yr 2-11-99

Pump test data: Well water was 20 gpm. Well water was 36 ft. after hours pumping gpm

Est. Yield: 20 gpm. Well water was 36 ft. after hours pumping gpm

Bore Hole Diameter: 11 in. to 36 ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped

1 Steel 3 RMP (SR) Welded

2 PVC 5 4 ABS 7 Fiberglass Threaded

Blank casing diameter: 26 in. Dia. 2.40 in. to ft. Dia. in. to ft.

Casing height above land surface: 12 in. weight 2.40 lbs./ft. Wall thickness or gauge No. 160psi

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement

1 Steel 3 Stainless steel 8 RMP (SR) 11 Other (specify)

2 Brass 4 Galvanized steel 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes

2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 26 ft. to 36 ft. From ft. to ft.

GRAVEL PACK INTERVALS: From 14 ft. to 36 ft. From ft. to ft.

6 GROUT MATERIAL: 3 Neat cement 14 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 14 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well

1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage

Direction from well? West How many feet? 120

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 12 clay

12 36 fine to medium sand

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-11-99 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 2-11-99 under the business name of Weninger Drilling Inc. by (signature) Wichele Goiges

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.