Lance			ED ACTION	Water Well Rec	ord Form WWC-				
ப்	TION OF WA		FRACTION			Section Number	Township Number	Range Number	
	Sedgw		SW 1/4		SW 1/4	34	т 26 s	R 1W E/W	
Distance and direction from nearest town or city street address of well if located within city?									
29th N. & Ridge Road, 3/8 m. E., N. side Wichita, Kansas WATER WELL OWNER: WICHITA, CITY OF									
RR#, ST. ADRESS, BOX#: 455 N. Main Board of Agriculture, Divivsion of Water Resource									
l	CITY, STATE, ZIP CODE: Wichita, Kansas						67203 Application Number: 980225		
LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL 50 ft. ELEVATION:									
MAN "X'	' IN SECTION	N BOX:	Depth(s) groun	dwater Encountered	1	ft.	2 ft.	3 ft.	
li				WATER LEVEL	•	. BELOW LAND	SURFACE MEASURED ON mo/day/yr	11/18/1998	
1	NW	NE			l water was	ft.	after hours pun	·. "	
ije			Est. Yield Bore Hole Diamete	61	ll water was to 50	ft. ft.	after hours pun and in.	- 0	
1 Mile		E	WELL WATER T		5 Public wate			to ft. Injection well	
			1 Domestic	3 Feedlot	6 Oil field w		•	Other (Specify below)	
	SW		2 Irrigation	4 Industrial	7 Lawn and	garden only	10 Monitoring well		
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was								no/day/yr sample was	
S submitted Water Well Disinfected? Yes X No									
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped									
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded									
2 PVC 4 ABS 7 Fiberglass SDR - 26 Threaded									
ì	sing Diam	•	in. to 20	ft., Dia	- in		ft., Dia in.	to ft.	
	0	e land surface [] N OR PERFORA			5.52	lbs. / ft. 7 PVC	Wall thickness or gauge No. 10 Asbestos-cem	.332	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREE	N OR PER	FORATION OP	ENING ARE:	5 Ga	uzed wrapped		8 Saw cut	11 None (open hole)	
1 Conti	nous slot	3 Mill si	lot		ire wrapped		9 Drilled holes		
2 Louve	red shutte	4 Key p	unched	7 To	rch cut		10 Other (specify)		
SCREE	N-PERFO	RATION INTERV	VALS: from 2	20	ft. to 50	ft., Fro	om ft. to	ft.	
from ft. to					ft. to	ft., Fro	om ft. to	ft.	
GRAVEL PACK INTERVALS: from 20 ft.					ft. to 50	ft., Fr	om ft. to	ft.	
from ft. to						ft., Fr		ft.	
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug Grout Intervals: From 0 ft. to 20 ft. From ft. to									
Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandon water well									
1 Septic tank 4 Lateral lines 7 Pit privy					,	11 Fuel storage		Oil well/Gas well	
2 Sewer lines 5 Cess pool				8 Sewage lagoon		ilizer storage 16	Other (specify below)		
3 Watertight sewer lines 6 Seepage pit 9 Feedyard					l	13 Insec	rticide storage	Apparent	
Direction from well? How many feet?									
FROM			LITHOLOGIC LO	G	FROM	то	PLUGGING INTE	RVALS	
0	10	fine sar							
10	20 40	medium s							
20 40	50	coarse s							
140	50	mearum s	sand		<u> </u>				
7 60	I CTC	DIC		This water well we	- (d) construe	4-d (0)	Amustad on (2) alument under		
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)									
Well Contractor's License No23.6									
Under the business name of Harp. Well. & Pump. Service. Inc by (signature)									