

1 LOCATION OF WATER WELL: Sedgwick	FRACTION NW 1/4 SE 1/4 SE 1/4	Section Number 19	Township Number T 26 S	Range Number R 1W E/W
---	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?
535 Atherton Maize, Kansas

WATER WELL OWNER: POWELL, Delbert RR#, ST. ADDRESS, BOX #: 535 Atherton CITY, STATE, ZIP CODE: Maize, Kansas	Board of Agriculture, Division of Water Resource Application Number:
---	---

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL 45 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. ft. WELL'S STATIC WATER LEVEL 20 FT. BELOW LAND SURFACE MEASURED ON 08/25/1999 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 45 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No
--	---

5 TYPE OF CASING USED:	1 Steel 3 RMP (SR) 2 PVC 4 ABS	5 Wrought iron 6 Asbestos-Cement 7 Fiberglass	8 Concrete tile 9 Other (Specify below) SDR-26	CASING JOINTS: X Clamped Welded Threaded
Blank casing Diameter 5 in. to 35 ft., Dia	in. to ft., Dia	in. to ft., Dia	in. to ft.	
Casing height above land surface 12 in., weight 2.35 lbs. / ft.	Wall thickness or gauge No. .214			
TYPE OF SCREEN OR PERFORATION MATERIAL:				
1 Steel 3 Stainless Steel 2 Brass 4 Galvanized steel	5 Fiberglass 6 Concrete tile	7 PVC 8 RMP (SR)	9 ABS 10 Asbestos-cement 11 other (specify)	12 None used (open hole)
SCREEN OR PERFORATION OPENING ARE:				
1 Continuous slot 3 Mill slot 2 Louvered shutter 4 Key punched	5 Gauzed wrapped 6 Wire wrapped 7 Torch cut	8 Saw cut 9 Drilled holes 10 Other (specify)	11 None (open hole)	
SCREEN-PERFORATION INTERVALS:				
	from 35	ft. to 45	ft., From	ft. to ft.
	from	ft. to	ft., From	ft. to ft.
GRAVEL PACK INTERVALS:				
	from 26	ft. to 45	ft., From	ft. to ft.
	from	ft. to	ft., From	ft. to ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other bentonite hole plug
Grout Intervals: From 4 ft. to 24 ft. From		ft. From	ft. to	ft. From 24 ft. to 26 ft.
What is the nearest source of possible contamination:				
1 Septic tank 4 Lateral lines 2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit	7 Pit privy 8 Sewage lagoon 9 Feedyard	10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage	14 Abandon water well 15 Oil well/Gas well 16 Other (specify below)	
Direction from well? West		How many feet? 70		

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	topsoil			
2	5	fine sand			
5	15	clay			
15	45	medium coarse sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 08/25/1999 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 08/27/99 Under the business name of Harp Well & Pump Service, Inc. by (signature)	<i>Todd S. Harp</i>
--	---------------------