			T an i carre		Water Well Reco	ord Form WWC-5				
1 LOCA	TION OF WA		FRACTIO				Section Number	Township Number	Range Number	
Sedgwick NE 1/4						SE 1/4	33	т 26 s	R 1W E/W	
Distance and direction frem nearest town or city street address of well if located within city?										
1/2 N. of 29th N., West side of Ridge Rd. Wichita, Kansas										
WATER WELL OWNER: WICHITA, CITY OF										
RR#, ST. ADRESS, BOX#: 455 N. Main Board of Agriculture, Divivsion of Water Resource									ivivsion of Water Resource	
CITY, STATE, ZIP CODE: Wichita, Kansa								Application Numb	Application Number: 990235	
	TE WELL'S I	OCATION WITH		F COMPLE		45	ft. El	LEVATION:		
A	IN SECTIO	N N		oundwater E		1	ft.	2 ft.	3 ft.	
			WELL'S STAT			7 FT	BELOW LAND S	SURFACE MEASURED ON mo/day/yr	12/10/1999	
'	NW	NE	Pui	np test data:	Well	water was	ft.	after hours pun	nping gpm	
يو	1 :		Est. Yield	gpn		l water was	ft.	after hours pun	nping gpm	
l ig w	/	E	Bore Hole Dian		. 2 in.	to 45	ft.	and in.	to ft.	
-	1		WELL WATER			5 Public wate			Injection well	
lт	sw	spc	1 Domestic		eedlot	6 Oil field wa		_	Other (Specify below)	
			2 Irrigation	•	dustrial	7 Lawn and g		10 Monitoring well		
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes,									no/day/yr sample was	
			submitted				W	ater Well Disinfected? Yes	X No	
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped									•	
1 Stee		3 RMP (SR)			sbestos-Cem	•	Other (Specify	•	Welded	
2 PVC 4 ABS 7 Fiberglass SDR - 26 Threaded										
Blank casing Diameter 8 in. to 20 ft., Dia in. to ft., Dia in. to ft.										
_	_		.2	in.,	weight		lbs. / ft.	Wall thickness or gauge No.	.332	
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)										
1 Ste		3 Stainless Steel	•		-		RMP (SR)	11 other (specif	•	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									• ′	
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wr										
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes										
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)										
SCREEN-PERFORATION INTERVALS: from 20 ft. to 45 ft., From ft. to ft.										
from ft. to						ft. to	ft., Fro	om ft. to	ft.	
GRAVEL PACK INTERVALS: from 20					ft. to 45		ft., Fro	om ft. to	ft.	
									ft.	
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug										
Grout Intervals: From ft. to ft. From ft. to ft. From 0 ft. to 20 ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandon water well										
1									Abandon water well	
1 Septic tank 4 Lateral lines					7 Pit privy		11 Fuel		Oll well/Gas well	
2 Sewer lines 5 Cess pool					8 Sewage lagoon			lizer storage 16	Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None Apparent										
	n from we		TTHOLOGIC	1.00			1	How many feet?		
FROM	то		LITHOLOGIC	LOG		FROM	TO	PLUGGING INTE	RVALS	
0 3	3 15	topsoil fine san	.a	****						
15	40	medium s								
	45		and							
40	4.5	clay				******		71		
						We obtain	<u> </u>	4-3	The state of the s	
			- N						-1-4-4-	
							1			
							· †			
		71.00							71	
								7.00		

				., ., .,	A-84			THE STATE OF THE S	****	
				90,00						
7 CO	VIDD + CT -	DICO		. This		(4)		4		
1 00	NTRACTO	on (mo/do://www.	R'S CERTIFICATIO	n: Thiswa1 1 ∩ / 1 Q Q	er well was 9	(1) construct	ed, (2) recons	tructed, or (3) plugged under the best of my knowledge and	my jurisdiction and	
Well C	ompieted Contractor	on (mo/day/year) r's license No	236	.7ک.ه	Water Well	and this rec	ompleted on (mo/day/yr) 19/1	J Dellet. Kansas Water 3 / 9 9	
Well Contractor's License No236										
		VIIII						Jodd)	Harr	