

1 LOCATION OF WATER WELL: Sedgwick		FRACTION SW 1/4 NW 1/4 NW 1/4		Section Number 34		Township Number T 26 S		Range Number R 1W E/W	
Distance and direction from nearest town or city street address of well if located within city? 1/8 m. S. of 37th N. on E. side of Ridge Road Wichita, KS.									
WATER WELL OWNER: WICHITA, CITY OF					Board of Agriculture, Division of Water Resource				
RR#, ST. ADDRESS, BOX #: 455 N. Main					Application Number: 20000022				
CITY, STATE, ZIP CODE: Wichita, Kansas 67202									
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 			4 DEPTH OF COMPLETED WELL 40 ft. ELEVATION:						
			Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.						
			WELL'S STATIC WATER LEVEL 5 FT. BELOW LAND SURFACE MEASURED ON 02/03/2000						
			Pump test data: Well water was ft. after hours pumping gpm						
Est. Yield gpm:			Well water was ft. after hours pumping gpm						
Bore Hole Diameter 12 in. to 40 ft. and in. to ft.									
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well									
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)									
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well									
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No									
5 TYPE OF CASING USED:									
1 Steel 3 RMP (SR)			5 Wrought iron 6 Asbestos-Cement			8 Concrete tile CASING JOINTS: Glued Clamped			
2 PVC 4 ABS			7 Fiberglass SDR-26			9 Other (Specify below) Welded Threaded			
Blank casing Diameter 8 in. to 20 ft., Dia in. to ft.									
Casing height above land surface 12 in., weight 5.52 lbs. / ft. Wall thickness or gauge No. .332									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless Steel 5 Fiberglass			6 Concrete tile 7 PVC 8 RMP (SR)			10 Asbestos-cement 11 other (specify)			
2 Brass 4 Galvanized steel			9 ABS			12 None used (open hole)			
SCREEN OR PERFORATION OPENING ARE:									
1 Continuous slot 3 Mill slot			5 Gauzed wrapped 6 Wire wrapped			8 Saw cut 11 None (open hole)			
2 Louvered shutter 4 Key punched			7 Torch cut			9 Drilled holes 10 Other (specify)			
SCREEN-PERFORATION INTERVALS: from 20 ft. to 40 ft., From ft. to ft.									
GRAVEL PACK INTERVALS: from 20 ft. to 40 ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug									
Grout Intervals: From ft. to ft. From ft. to ft. From ft. to ft. From 0 ft. to 20 ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy			8 Sewage lagoon 9 Feedyard			10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandon water well 15 Oil well/Gas well 16 Other (specify below) None Apparent			
Direction from well? How many feet?									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0	3	topsoil sandy							
3	15	fine sand							
15	35	medium sand							
35	40	coarse sand							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 02/03/00 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 02/07/00 Under the business name of Harp Well & Pump Service, Inc. by (signature) Todd S. Harp									