

1 LOCATION OF WATER WELL:		FRACTION		Section Number		Township Number		Range Number	
Sedgwick		SE 1/4 SW 1/4 SW 1/4		34		T 26 S		R 1W E/W	
Distance and direction from nearest town or city street address of well if located within city?									
1/4 E. of Ridge Road on N. side of 29th St. N. Wichita, Kansas									
WATER WELL OWNER: WICHITA, CITY OF									
RR#, ST. ADDRESS, BOX #: 455 N. Main									
CITY, STATE, ZIP CODE: Wichita, Kansas 67202									
Board of Agriculture, Division of Water Resource									
Application Number: 20000029									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 40 ft. ELEVATION:							
		Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. ft.							
		WELL'S STATIC WATER LEVEL 8 FT. BELOW LAND SURFACE MEASURED ON 02/15/2000							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 12 in. to 40 ft. and in. to ft.							
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
Was a chemical/bacteriological sample submitted to Department? Yes No ☒ ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes ☒ No									
5 TYPE OF CASING USED:									
1 Steel 3 RMP (SR)		5 Wrought iron 6 Asbestos-Cement		8 Concrete tile 9 Other (Specify below)		CASING JOINTS: Glued ☒ Clamped		Welded	
2 PVC 4 ABS		7 Fiberglass		SDR-26		Threaded			
Blank casing Diameter 8 in. to 20 ft., Dia in. to ft., Dia in. to ft.									
Casing height above land surface 12 in., weight 5.52 lbs./ft. Wall thickness or gauge No. .332									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless Steel		5 Fiberglass		7 PVC 8 RMP (SR)		10 Asbestos-cement		11 other (specify)	
2 Brass 4 Galvanized steel		6 Concrete tile		9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENING ARE:									
1 Continuous slot 3 Mill slot		5 Gauzed wrapped 6 Wire wrapped		8 Saw cut 9 Drilled holes		11 None (open hole)			
2 Louvered shutter 4 Key punched		7 Torch cut		10 Other (specify)					
SCREEN-PERFORATION INTERVALS: from 20 ft. to 40 ft., From ft. to ft.									
GRAVEL PACK INTERVALS: from 20 ft. to 40 ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug									
Grout Intervals: From ft. to ft. From ft. to ft. From 0 ft. to 20 ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines		7 Pit privy		10 Livestock pens 11 Fuel storage		14 Abandon water well		15 Oil well/Gas well	
2 Sewer lines 5 Cess pool		8 Sewage lagoon		12 Fertilizer storage		16 Other (specify below)			
3 Watertight sewer lines 6 Seepage pit		9 Feedyard		13 Insecticide storage		None Apparent			
Direction from well? How many feet?									
FROM TO LITHOLOGIC LOG			FROM TO PLUGGING INTERVALS						
0 3 sandy topsoil									
3 20 fine sand									
20 35 medium sand									
35 40 coarse sand									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 02/15-2000 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 02/16/00 Under the business name of Harp Well & Pump Service, Inc. by (signature) Todd S. Harp									