

1 LOCATION OF WATER WELL: Sedgwick	FRACTION NW 1/4 NW 1/4 SW 1/4	Section Number 34	Township Number T 26 S	Range Number R 1W E/W
--	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

1/2 N. of of 29th N. & Ridge Rd., E. side Wichita, KS.

WATER WELL OWNER: WICHITA, CITY OF	Board of Agriculture, Division of Water Resource
RR#, ST. ADDRESS, BOX #: 455 N. Main	Application Number: 990268
CITY, STATE, ZIP CODE: Wichita, Kansas 67202	

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF plugged WELL 45 ft. ELEVATION:
	Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. ft.
	WELL'S STATIC WATER LEVEL 12 FT. BELOW LAND SURFACE MEASURED ON 03/20/2000
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm : Well water was ft. after hours pumping gpm
Bore Hole Diameter in. to ft. and in. to ft.	
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted	Water Well Disinfected? Yes X No

5 TYPE OF CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS:	Glued	Clamped
1 Steel 3 RMP (SR)	6 Asbestos-Cement	9 Other (Specify below)		Welded	
2 PVC 4 ABS	7 Fiberglass			Threaded	
Blank casing Diameter 8 in. to ft. , Dia in. to ft. , Dia in. to ft.					
Casing height below land surface 36 in., weight lbs. / ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement			
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify) N/A					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENING ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)		
1 Continuous slot 3 Mill slot 6 Wire wrapped		9 Drilled holes			
2 Louvered shutter 4 Key punched 7 Torch cut		10 Other (specify) N/A			
SCREEN-PERFORATION INTERVALS: from ft. to ft. , From ft. to ft.					
GRAVEL PACK INTERVALS: from ft. to ft. , From ft. to ft.					

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug
Grout Intervals: From 3 ft. to 9 ft. From ft. to ft. From ft. to ft. From ft. to ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandon water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
None Apparent

Direction from well?	How many feet?
FROM TO LITHOLOGIC LOG	FROM TO PLUGGING INTERVALS
	0 3 surface clay and silt
	3 9 cement grout
	9 12 bentonite hole plug
	12 45 chlorinated sand and gravel

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) <u>plugged</u> under my jurisdiction and was completed on (mo/day/year) 03/20/00 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 03/22/00
Under the business name of Harp Well & Pump Service, Inc. by (signature) Todd S. Harp