

1 LOCATION OF WATER WELL: Sedgwick	FRACTION NW 1/4 SW 1/4 NW 1/4	Section Number 34	Township Number T 26 S	Range Number R 1W E/W
Distance and direction from nearest town or city street address of well if located within city? 3/4 m. N. of 29th N. on East side of Ridge Rd. Wichita, KS.				
WATER WELL OWNER: WICHITA, CITY OF RR#, ST. ADDRESS, BOX #: 455 N. Main CITY, STATE, ZIP CODE: Wichita, Kansas 67202		Board of Agriculture, Division of Water Resource Application Number: 20000016		
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF plugged WELL 40 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 6 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 04/11/2000 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm : Well water was ft. after hours pumping gpm Bore Hole Diameter in. to ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes ☐ No ☒ ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes ☒ No ☐			
5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (Specify below) Welded Blank casing Diameter 8 in. to ft. , Dia in. to ft. , Dia in. to ft. Casing height below land surface 36 in., weight lbs. / ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify) N/A 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENING ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) N/A SCREEN-PERFORATION INTERVALS: from ft. to ft. , From ft. to ft. GRAVEL PACK INTERVALS: from ft. to ft. , From ft. to ft.				
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug Grout Intervals: From 3 ft. to 7 ft. From ft. to ft. From ft. to ft. From 7 ft. to 12 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandon water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage None Apparent Direction from well? How many feet?				
FROM		TO		LITHOLOGIC LOG
FROM		TO		PLUGGING INTERVALS
		0	3	surface sand and silt
		3	7	cement grout
		7	12	bentonite hole plug
		12	40	chlorinated sand and gravel
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) <u>plugged</u> under my jurisdiction and was completed on (mo/day/year) 04/11/00 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 04/14/00 Under the business name of Harp Well & Pump Service, Inc. by (signature) Todd S. Harp				