

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Seagwick</u>		<u>NW 1/4 NE 1/4 SE 1/4</u>	<u>1a</u>	<u>T 24E</u>	<u>R 1 EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>109 W. Central - Maize</u>					
2 WATER WELL OWNER: <u>Jim Downing</u>		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # <u>212 W. 4th</u>		Application Number:			
City, State, ZIP Code <u>Eugenwood, KS 67526</u>					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>51</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>18</u> ft. 2. <u>51</u> ft. 3. <u>518-01</u> ft.			
		WELL'S STATIC WATER LEVEL <u>18</u> ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was <u>20</u> gpm. Well water was <u>51</u> ft. after <u>5</u> hours pumping <u>518-01</u> gpm			
		Est. Yield <u>20</u> gpm. Well water was <u>51</u> ft. after <u>5</u> hours pumping <u>518-01</u> gpm			
		Bore Hole Diameter <u>11</u> in. to <u>51</u> ft. and <u>51</u> in. to <u>51</u> ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u>X</u>		If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued <u>X</u> Clamped <u>X</u>			
1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 8 Concrete tile 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)			
Blank casing diameter <u>5</u> in. to <u>43</u> ft. Dia. <u>2.40</u> in. to <u>160PSI</u> lbs./ft. Wall thickness or gauge No. <u>160PSI</u>					
Casing height above land surface <u>12</u> in. weight <u>2.40</u> lbs./ft.					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From <u>18</u> ft. to <u>51</u> ft.					
GRAVEL PACK INTERVALS: From <u>18</u> ft. to <u>51</u> ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From <u>3</u> ft. to <u>18</u> ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? <u>north</u>		How many feet? <u>50</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	15	clay			
15	51	fine to med. sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>3-18-01</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>318</u> This Water Well Record was completed on (mo/day/yr) <u>5-18-01</u> under the business name of <u>Weninger Drilling Inc.</u> by (signature) <u>Michael Gray</u>					