

1] LOCATION OF WATER WELL: County: Sedgewick Fraction: SW 1/4 SE 1/4 NE SW 1/4 Section Number: 34 Township Number: 26S Range Number: 1E

Distance and direction from nearest town or city street address of well if located within city? 3213 Northshore Ct.

2] WATER WELL OWNER: Frank & Kim McCormick

RR#, St. Address, Box #: 8827 West meadow Park

City, State, ZIP Code: Wichita, KS 67205

Board of Agriculture, Division of Water Resources

Application Number:

3] LOCATE WELL'S LOCATION WITH 4] DEPTH OF COMPLETED WELL: 36 ft. ELEVATION: 12-7-01

AN "X" IN SECTION BOX:

Depth(s) Groundwater Encountered: 1. 12 ft. 2. 36 ft. 3. 12-7-01 ft.

WELL'S STATIC WATER LEVEL: 12 ft. below land surface measured on mo/day/yr

Rump test data: Well water was 11 ft. after 36 hours pumping 12-7-01 gpm

Est. Yield: 26 gpm; Well water was 36 ft. after 36 hours pumping 12-7-01 gpm

Bore Hole Diameter: 11 in. to 36 ft., and 36 in. to 12-7-01 ft.

WELL WATER TO BE USED AS:

5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes. No. If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes. No.

5] TYPE OF BLANK CASING USED:

1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued. X Clamped.

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded

Blank casing diameter: 5 in. to 26 ft., Dia. 240 in. to 160 psi

Casing height above land surface: 12 in., weight 240 lbs./ft. Wall thickness or gauge No. 160 psi

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes

10 Other (specify) 10 Other (specify) ft.

SCREEN-PERFORATED INTERVALS: From 26 ft. to 36 ft., From 36 ft. to 12-7-01 ft.

GRAVEL PACK INTERVALS: From 12 ft. to 36 ft., From 36 ft. to 12-7-01 ft.

6] GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 12 ft., From 12 ft. to 12-7-01 ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

Direction from well? south

How many feet? 25

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 to 6 clay

6 to 36 med sand

7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-7-01 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 318 This Water Well Record was completed on (mo/day/yr) 12-7-01 under the business name of Werninger Drilling Inc. by (signature) Michelle Gorgal

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone 785-296-5524. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.