

1 LOCATION OF WATER WELL: Sedgwick		FRACTION NW 1/4 SW 1/4 SW 1/4		Section Number 33	Township Number T 26 S	Range Number R 1W E/W
Distance and direction from nearest town or city street address of well if located within city? 8601 Shadow Lakes Wichita, Kansas						
WATER WELL OWNER: BRUNNER, Steve RR#, ST. ADDRESS, BOX #: 8601 Shadow Lakes CITY, STATE, ZIP CODE: Wichita, Kansas				Board of Agriculture, Division of Water Resource Application Number:		
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL 85 ft. ELEVATION:				
		Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.				
		WELL'S STATIC WATER LEVEL 40 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 6-11-2002				
		Pump test data: Well water was ft. after hours pumping gpm				
Est. Yield gpm: Well water was ft. after hours pumping gpm		Bore Hole Diameter 12 in. to 85 ft. and in. to ft.				
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well				
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well				
Was a chemical/bacteriological sample submitted to Department? Yes ☐ No ☒ ; If yes, mo/day/yr sample was submitted						
Water Well Disinfected? Yes ☒ No ☐						
5 TYPE OF CASING USED:						
1 Steel 3 RMP (SR)		5 Wrought iron 6 Asbestos-Cement		8 Concrete tile 9 Other (Specify below)		CASING JOINTS: Glued ☒ Clamped
2 PVC 4 ABS		7 Fiberglass		SDR-26		Welded Threaded
Blank casing Diameter 5 in. to 65 ft., Dia in. to ft.,		weight 2.35 lbs. / ft.		Wall thickness or gauge No. .214		
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1 Steel 3 Stainless Steel		5 Fiberglass		8 RMP (SR)		11 other (specify)
2 Brass 4 Galvanized steel		6 Concrete tile		9 ABS		12 None used (open hole)
SCREEN OR PERFORATION OPENING ARE:						
1 Continuous slot 3 Mill slot		5 Gauzed wrapped 6 Wire wrapped		8 Saw cut 11 None (open hole)		
2 Louvered shutter 4 Key punched		7 Torch cut		9 Drilled holes 10 Other (specify)		
SCREEN-PERFORATION INTERVALS: from 65 ft. to 85 ft., From ft. to ft.						
GRAVEL PACK INTERVALS: from 24 ft. to 85 ft., From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug						
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft.						
What is the nearest source of possible contamination:						
1 Septic tank 4 Lateral lines		7 Pit privy		10 Livestock pens 14 Abandon water well		
2 Sewer lines 5 Cess pool		8 Sewage lagoon		11 Fuel storage 15 Oil well/Gas well		
3 Watertight sewer lines 6 Seepage pit		9 Feedyard		12 Fertilizer storage 16 Other (specify below)		
Direction from well? Southwest How many feet? 60						
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS						
0	4	topsoil				
4	30	clay				
30	45	fine sand				
45	50	clay				
50	60	medium coarse sand				
60	85	medium sand				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-11-2002 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 6-12-2002 Under the business name of Harp Well & Pump Service, Inc by (signature) <i>Todd S. Harp</i>						