

1 LOCATION OF WATER WELL: Fraction <u>NE 1/4 SW 1/4 NE 1/4</u> Section Number <u>24</u> Township Number <u>T 26 S</u> Range Number <u>R 1</u> (NW)	
County: <u>Bellevue</u> Distance and direction from nearest town or city street address or well if located within city? <u>4909 Harborside</u>	
2 WATER WELL OWNER: <u>Mr. Summit</u> RR#, St. Address, Box # : <u>4909 Harborside</u> City, State, ZIP Code : <u>Wichita KS 67204</u> Board of Agriculture, Division of Water Resources Application Number: <u>none</u>	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL <u>35</u> ft. ELEVATION: <u>1300</u>
	Depth(s) Groundwater Encountered <u>1</u> ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL <u>15</u> ft. below land surface measured on mo/day/yr <u>4-7-09</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial <u>7</u> Domestic (lawn & garden) 10 Monitoring well
	Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No <u>X</u>
	5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <u>5</u> in. to <u>2.5</u> ft. Dia in. to ft. Dia in. to ft. Casing height above land surface <u>12</u> in., weight lbs./ft. Wall thickness or gauge No. <u>160</u>
	TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify) 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Mill slot 3 Guazed wrapped 4 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) ft.
SCREEN-PERFORATED INTERVALS: From <u>25</u> ft. to <u>35</u> ft., From ft. to ft. GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft. <u>none</u>	6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From <u>0</u> ft. to <u>150</u> ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? <u>South</u> 13 Insecticide storage How many feet? <u>15</u>
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS <u>09 9 Top Soil</u> <u>9 20 Fine Tan Sand</u> <u>20 35 Coarse Tan Sand</u>	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>4-7-09</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No <u>472</u> This Water Well Record was completed on (mo/day/yr) <u>4-7-09</u> under the business name of <u>B. Gordon Pump & Well</u> by (signature) <u>David Bab</u>	