

Form WWC-5 KSA 82a-1212

LOCATION OF WATER WELL:

FRACTION

SECTION NUMBER

TOWNSHIP NUMBER

RANGE NUMBER

Sedgwick

SE 1/4 SE 1/4 SW 1/4

28

T 26 S

R 1W E/W

Distance and direction from nearest town or city street address of well if located within city?

Intersection of Tyler and 37th North, 3/8 mile E. on North side

Wichita, Kansas

WATER WELL OWNER:

RR#,ST. ADDRESS,BOX #:

CITY, STATE:

WICHITA CITY OF

455 N. Main

Wichita, Kansas

Board of Agriculture, Division of Water Resource

Application Number:

20030273

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

1 Mile

N

W

E

S

DEPTH OF WELL:

ELEVATION:

45

ft.

ft.

ft.

Depth of groundwater Encountered:

ft.

ft.

ft.

WELL'S STATIC WATER LEVEL

12

FT. BELOW LAND SURFACE MEASURED ON

mo/day/yr:

6/3/04

Pump test data:

Well water was

ft. after

hours of pumping @

gpm

Est. Yield:

gpm

Well water was

ft. after

hours of pumping @

gpm

Bore Hole Diameter

in.

to

ft.

and

in.

to

ft.

WELL WATER WAS USED AS:

1. Domestic

3. Feedlot

5. Public water supply

7. Lawn and garden only

9. Dewatering

11. Injection well

2. Irrigation

4. Industrial

6. Oil field water supply

8. Air conditioning

10. Monitoring well

12. Other (Specify below)

Was a chemical/bacteriological sample submitted to Department?

YES

NO

If yes, what mo/day/yr was sample submitted

Was Water Well Disinfected?

YES

NO

TYPE OF CASING USED:

1. Steel

3. RPM (SR)

5. Wrought Iron

7. Fiberglass

9. Other (Specify below)

CASING JOINTS:

Glued

Threaded

2. PVC

4. ABS

6. Asbestos-Cement

8. Concrete tile

Welded

Clamped

Blank casing diameter

8

in.

to

ft.

Dia.

in.

to

ft.

Dia.

in.

to

ft.

Casing height below land surface:

36

in.

Weight:

lbs. / ft.

Wall thickness or gauge No.

in.

TYPE OF SCREEN OR PERFORATION MATERIAL:

1. Steel

3. Stainless Steel

5. Fiberglass

7. PVC

9. ABS

11. Other (specify)

N/A

2. Brass

4. Galvanized

6. Concrete Tile

8. RMP (SR)

10. Asbestos-Cement

12. None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1. Continuous slot

3. Mill slot

5. Gauzed wrapped

7. Torch cut

9. Drilled holes

11. None (open hole)

2. Louvered shutter

4. Key punched

6. Wire wrapped

8. Saw cut

10. Other (specify)

N/A

SCREEN - PERFORATION INTERVAL

From

ft.

to

ft.

From

ft.

to

ft.

GRAVEL PACK INTERVALS:

From

ft.

to

ft.

From

ft.

to

ft.

GROUT MATERIALS:

1. Neat cement

2. Cement Grout

3. Bentonite

Other

bentonite hole plug

Grout Intervals:

From

ft.

to

ft.

From

ft.

to

ft.

From

3

ft.

to

23

ft.

What is the nearest source of possible contamination:

1. Septic tank

4. Lateral lines

7. Pit privy

10. Livestock pens

13. Insecticide storage

15. Oil well/Gas well

2. Sewer lines

5. Cess Pool

8. Sewage lagoon

11. Fuel storage

14. Abandon water well

16. Other (specify below)

3. Watertight sewer line

6. Seepage pit

9. Feed yard

12. Fertilizer storage

None Apparent

Direction from well?

How many feet?

From

To

LITHOLOGIC LOG

From

To

LITHOLOGIC LOG

0

3

surface sandy clay

3

23

bentonite hole plug

23

45

chlorinated sand & gravel

Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 6/3/04 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 6/7/04

under the business name of Harp Well & Pump Service Inc. by (signature) Todd S. Harp