

1 LOCATION OF WATER WELL: Fraction 1/4 NW 1/4 NW Section Number 23 Township Number 26 Range Number 16  
County Sedgwick Distance and direction from nearest town or city street address of well if located within city? 3438 N. Peppardge

2 WATER WELL OWNER: Lloyd Eashor  
RR#, St. Address, Box # :  
City, State, ZIP Code :  
Board of Agriculture, Division of Water Resources  
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
N  
NW NE  
W SE  
S

4 DEPTH OF COMPLETED WELL 63 ft. ELEVATION: 7-14-04  
Depth(s) Groundwater Encountered: 1 15 ft. 2 ft. 3 ft.  
WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr  
Pump test data: Well water was ft. after hours pumping gpm  
Est. Yield 25 gpm: Well water was ft. after hours pumping gpm  
WELL WATER TO BE USED AS:  
1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 5 Public water supply 6 Oil field water supply 7 Domestic (lawn & garden) 8 Air conditioning 9 Dewatering 10 Monitoring well 11 Injection well 12 Other (Specify below)  
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted  
Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:  
1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued X Clamped Welded Threaded  
Blank casing diameter 2 in. Dia 240 in. to ft. Dia 100 ft.  
Casing height above land surface 2 in., weight 240 lbs./ft. Wall thickness or gauge No. 100 psi  
TYPE OF SCREEN OR PERFORATION MATERIAL:  
1 Steel 2 Brass 3 Stainless Steel 4 Galvanized Steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole)  
SCREEN OR PERFORATION OPENINGS ARE:  
1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Guazed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)  
SCREEN-PERFORATED INTERVALS: From 0 ft. to 2 ft. From 2 ft. to 10 ft. From 10 ft. to 15 ft. From 15 ft. to 63 ft.  
GRAVEL PACK INTERVALS: From 0 ft. to 2 ft. From 2 ft. to 10 ft. From 10 ft. to 15 ft. From 15 ft. to 63 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
Grout Intervals: From 0 ft. to 2 ft. From 2 ft. to 10 ft. From 10 ft. to 15 ft. From 15 ft. to 63 ft.  
What is the nearest source of possible contamination:  
1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)  
Direction from well? NW How many feet? 50

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-14-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 38 This Water Well Record was completed on (mo/day/yr) 7-14-04 under the business name of Winthrop Drilling Inc. by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.