

1 LOCATION OF WATER WELL County: <u>Seago</u> <u>NE 1/4 SE 1/4</u> Section Number <u>32</u> Township Number <u>260</u> Range Number <u>24</u>					
Distance and direction from nearest town or city street address of well, if located within city? <u>lot # 116 in Fox Ridge on Hallon Street</u>					
2 WATER WELL OWNER: <u>Leetoch</u> RR#, St. Address, Box # : City, State, ZIP Code : Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL <u>65</u> ft. ELEVATION: Depth(s) Groundwater Encountered <u>28</u> ft. 2 ft. WELL'S STATIC WATER LEVEL <u>28</u> ft. below land surface measured on mo/day/yr <u>8-13-04</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield <u>20</u> gpm Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 2 Irrigation 4 Industrial 6 Oil field water supply 8 Air conditioning 11 Injection well 9 Dewatering 12 Other (Specify below) <u>7 Domestic (lawn & garden)</u> 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No				
5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued <u>X</u> Clamped Welded Threaded Blank casing diameter <u>5</u> in. to <u>55</u> ft., Dia <u>2.40</u> in. to ft., Dia in. to ft. Casing height above land surface <u>12</u> in., weight <u>2.40</u> lbs./ft. Wall thickness or gauge No. <u>160PS</u> TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless Steel 4 Galvanized Steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Guazed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) ft. 11 None (open hole) SCREEN-PERFORATED INTERVALS: From <u>55</u> ft. to <u>65</u> ft., From ft. to ft. GRAVEL PACK INTERVALS: From <u>28</u> ft. to <u>65</u> ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From <u>3</u> ft. to <u>28</u> ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) <u>open</u> Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	topsoil			
3	20	clay			
20	25	fine sand			
25	45	clay			
45	50	fine to med sand			
50	60	clay			
60	65	med sand			
		clay			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>8-13-04</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No <u>318</u> This Water Well Record was completed on (mo/day/yr) <u>8-13-04</u> under the business name of <u>Weniger Brothers Inc</u> by (signature) <u>Michael J. Weniger</u>					

RECEIVED

SEP 07 2004

BUREAU OF WATER