


1 LOCATION OF WATER WELL County: <u>Sedgewick</u> Fraction <u>NW 1/4 NE 1/4 SE 1/4</u> Section Number <u>32</u> Township Number <u>T 26 S</u> Range Number <u>R 1 E</u>	
Distance and direction from nearest town or city street address of well if located within city? <u>4011 Silver Hollow Ct.</u>	
2 WATER WELL OWNER <u>Shawn Kordonowy</u> RR#, St. Address, Box # : City, State, ZIP Code : Board of Agriculture, Division of Water Resources Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL <u>65</u> ft. ELEVATION: Depth(s) Groundwater Encountered <u>1</u> ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL <u>18</u> ft. below land surface measured on mo/day/yr <u>8-9-04</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield <u>25</u> gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) <u>7 Domestic (lawn & garden)</u> 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded Blank casing diameter <u>5</u> in. to <u>8</u> ft., Dia <u>2.40</u> in. to ft., Dia in. to ft. Casing height above land surface <u>10</u> in., weight <u>2.40</u> lbs./ft. Wall thickness or gauge No. <u>160 psi</u> TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify) 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) ft. SCREEN-PERFORATED INTERVALS: From <u>55</u> ft. to <u>65</u> ft., From ft. to ft. GRAVEL PACK INTERVALS: From <u>18</u> ft. to <u>65</u> ft., From ft. to ft. From ft. to ft., From ft. to ft.	
6 GROUT MATERIAL: 1 Neat cement 3 Bentonite 4 Other Grout Intervals: From <u>3</u> ft. to <u>18</u> ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? <u>East</u> How many feet? <u>12</u>	
FROM TO LITHOLOGIC LOG	FROM TO PLUGGING INTERVALS
0 1	topsoil
1 20	clay
20 36	fine sand
36 46	med sand
46 52	clay
52 62	med sand
62 65	clay
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>8-9-04</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. <u>318</u> This Water Well Record was completed on (mo/day/yr) <u>8-13-04</u> under the business name of <u>Weninger Drilling Inc.</u> by (signature) <u>Daniel George</u>	
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.	

RECEIVED

SEP 07 2004

BUREAU OF WATER