

1	LOCATION OF WATER WELL: Sedgwick	FRACTION SW 1/4 SE 1/4 SW 1/4	SECTION NUMBER 33	TOWNSHIP NUMBER T 26 S	RANGE NUMBER R 1W E/W
---	--	---	-----------------------------	---------------------------	--------------------------

Distance and direction from nearest town or city street address of well if located within city?

8605 W. 34th N. Ct. Wichita, Kansas

2	WATER WELL OWNER:	HUNDLEY, Becky			Board of Agriculture, Division of Water Resource
	RR#,ST. ADDRESS,BOX #:	8605 W. 34th N. Ct.			
	CITY, STATE:	Wichita, Kansas		ZIP CODE:	

3 LOCATE WELL'S LOCATION
WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL:		65		ft.		ELEVATION:			
Depth of groundwater Encountered:				ft.				ft.	
WELL'S STATIC WATER LEVEL		25		FT. BELOW LAND SURFACE MEASURED ON		mo/day/yr:		9/3/04	
Pump test data:		Well water was				ft. after		hours of pumping @	
Est. Yield:		gpm		Well water was		ft. after		hours of pumping @	
Bore Hole Diameter		12		in.		to 65		ft.	
				and				in.	
								to	
								ft.	
WELL WATER TO BE USED AS:									
1. Domestic		3. Feedlot		5. Public water supply		7. Lawn and garden only		9. Dewatering	
								11. Injection well	
2. Irrigation		4. Industrial		6. Oil field water supply		8. Air conditioning		10. Monitoring well	
								12. Other (Specify below)	
Was a chemical/bacteriological sample submitted to Department?		YES		NO				If yes, what mo/day/yr was sample submitted	
						Was Water Well Disinfected?		YES	
								NO	

5	TYPE OF CASING USED:				CASING JOINTS:		Threaded
	1. Steel	3. RPM (SR)	5. Wrought Iron	7. Fiberglass	9. Other (Specify below)	Glued	Clamped
	2. PVC	4. ABS	6. Asbestos-Cement	8. Concrete tile	SDR-26	Welded	
	Blank casing diameter 5 in.		to 45 ft.,		Dia. in.		to ft.
	Casing height above land surface: 16 in.,		Weight: 2.35 lbs. / ft.		Wall thickness or gauge No.		.214
	TYPE OF SCREEN OR PERFORATION MATERIAL:						
	1. Steel	3. Stainless Steel	5. Fiberglass	7. PVC	9. ABS	11. Other (specify)	
	2. Brass	4. Galvanized	6. Concrete Tile	8. RMP (SR)	10. Asbestos-Cement	12. None used (open hole)	
	SCREEN OR PERFORATION OPENINGS ARE:						
	1. Continuous slot	3. Mill slot	5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)	
	2. Louvered shutter	4. Key punched	6. Wire wrapped	8. Saw cut	10. Other (specify)		
	SCREEN - PERFORATION INTERVAL		From 45 ft.	to 65 ft.,	From ft.	to ft.	
			From ft.	to ft.,	From ft.	to ft.	
	GRAVEL PACK INTERVALS:		From 24 ft.	to 65 ft.,	From ft.	to ft.	
			From ft.	to ft.,	From ft.	to ft.	

6	GROUT MATERIALS:												
	1. Neat cement			2. Cement Grout			3. Bentonite			Other bentonite hole plug			
	Grout Intervals:	From	4 ft.	to	24 ft.,	From	ft.	to	ft.,	From	ft.	to	ft.
	What is the nearest source of possible contamination:												
	1. Septic tank		4. Lateral lines		7. Pit privy		10. Livestock pens		13. Insecticide storage		15. Oil well/Gas well		
	2. Sewer lines		5. Cess Pool		8. Sewage lagoon		11. Fuel storage		14. Abandon water well		16. Other (specify below)		
	3. <u>Watertight sewer line</u>		6. Seepage pit		9. Feed yard		12. Fertilizer storage						
	Direction from well? East								How many feet? 15				

From	To	LITHOLOGIC LOG	From	To	LITHOLOGIC LOG
0	4	topsoil			
4	20	sandy clay			
20	31	sand			
31	38	clay			
38	65	sand			
					RECEIVED
					OCT 04 2004
					BUREAU OF WATER

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. **reconstructed** or 3. **plugged** under my jurisdiction and was completed on (mo/day/year) **9/3/2004** and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. **236** This water well record was completed on (mo/day/year) **9/6/2004**

under the business name of **Harp Well & Pump Service Inc.** by (signature) *[Signature]*