

1	LOCATION OF WATER WELL: Sedgwick	FRACTION NE 1/4 NW 1/4 SE 1/4	SECTION NUMBER 33	TOWNSHIP NUMBER T 26 S	RANGE NUMBER R 1W E/W
---	--	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

3350 N. Wildrose Ct. Wichita, Kansas

2	WATER WELL OWNER:	DAVIS, Derrick	
	RR#,ST. ADDRESS,BOX #:	3350 N. Wildrose Ct.	Board of Agriculture, Division of Water Resource
	CITY, STATE:	Wichita, Kansas	Application Number:
		ZIP CODE:	

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 50 ft. Depth of groundwater Encountered: _____ ft. WELL'S STATIC WATER LEVEL 12 FT. BELOW LAND SURFACE MEASURED ON 3/12/05 Pump test data: Well water was _____ ft. after _____ hours of pumping @ _____ gpm Est. Yield: _____ gpm Well water was _____ ft. after _____ hours of pumping @ _____ gpm Bore Hole Diameter 12 in. to 50 ft. and _____ in. to _____ ft.	ELEVATION: _____ ft.
	WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below)	
	Was a chemical/bacteriological sample submitted to Department? YES NO submitted Was Water Well Disinfected? YES NO	

TYPE OF CASING USED:				CASING JOINTS:			
1. Steel	3. RPM (SR)	5. Wrought Iron	7. Fiberglass	9. Other (Specify below)	☒ Glued ☐ Welded		
☒ 2. PVC	4. ABS	6. Asbestos-Cement	8. Concrete tile	SDR-26			
Blank casing diameter		5 in.	to 30 ft.,	Dia.	in.	to	ft.,
Casing height above land surface:		12 in.,	Weight:	2.35 lbs. / ft.	Wall thickness or gauge No.		.214
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1. Steel	3. Stainless Steel	5. Fiberglass	☒ 7. PVC	9. ABS	11. Other (specify)		
2. Brass	4. Galvanized	6. Concrete Tile	8. RMP (SR)	10. Asbestos-Cement	12. None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:							
1. Continuous slot	3. Mill slot	5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)		
2. Louvered shutter	4. Key punched	6. Wire wrapped	☒ 8. Saw cut	10. Other (specify)			
SCREEN - PERFORATION INTERVAL		From	30 ft.	to	50 ft.,	From	ft.
		From	ft.	to	ft.,	From	ft.
GRAVEL PACK INTERVALS:		From	24 ft.	to	50 ft.,	From	ft.
		From	ft.	to	ft.,	From	ft.

6	GROUT MATERIALS:		1. Neat cement	2. Cement Grout	3. Bentonite	Other	bentonite hole plug		
	Grout Intervals:	From	4 ft.	to	24 ft.,	From	ft.	to	ft.
	What is the nearest source of possible contamination:								
	1. Septic tank	4. Lateral lines	7. Pit privy	10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well			
	2. Sewer lines	5. Cess Pool	8. Sewage lagoon	11. Fuel storage	14. Abandon water well	16. Other (specify below)			
	3. Watertight sewer line	6. Seepage pit	9. Feed yard	12. Fertilizer storage					
Direction from well?		East			How many feet?		15		

[illegible]

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 3/12/2005 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 3/14/2005

under the business name of Harp Well & Pump Service Inc. by (signature) Jo dd S. Harp