

1	LOCATION OF WATER WELL: Sedgwick	FRACTION SE 1/4 NE 1/4 NE 1/4	SECTION NUMBER 33	TOWNSHIP NUMBER T 26 S	RANGE NUMBER R 1W E/W
---	--	---	-----------------------------	----------------------------------	---------------------------------

2	WATER WELL OWNER:	KLAUSMEYER CONSTRUCTION		
	RR#,ST. ADDRESS,BOX #:	10008 W. York		
	CITY, STATE:	Wichita, Kansas	ZIP CODE:	

Board of Agriculture, Division of Water Resource
 Application Number:

WELL'S LOCATION IN SECTION BOX:

Depth of groundwater Encountered: 10 ft. BELOW LAND SURFACE MEASURED ON 4/4/05

WELL'S STATIC WATER LEVEL 10 FT. BELOW LAND SURFACE MEASURED ON 4/4/05

Pump test data: Well water was _____ ft. after _____ hours of pumping @ _____ gpm

Est. Yield: _____ gpm Well water was _____ ft. after _____ hours of pumping @ _____ gpm

Bore Hole Diameter 12 in. to 42 ft. and _____ in. to _____ ft.

WELL WATER TO BE USED AS:

1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well

2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted _____

Was Water Well Disinfected? YES NO

TYPE OF CASING USED: 1. Steel 2. <u>PVC</u> 3. RPM (SR) 4. ABS 5. Wrought Iron 6. Asbestos-Cement 7. Fiberglass 8. Concrete tile 9. Other (Specify below)		CASING JOINTS: 11. <u>Glued</u> 12. Welded Threaded Clamped	
Blank casing diameter 5 in. to 30 ft., Dia. in. to ft., Dia. in. to ft.		SDR-26	
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. <u>PVC</u> 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. <u>Saw cut</u> 10. Other (specify)			
SCREEN - PERFORATION INTERVAL From 30 ft. to 42 ft., From ft. to ft.			
From ft. to ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 24 ft. to 42 ft., From ft. to ft.			
From ft. to ft., From ft. to ft.			

6	GROUT MATERIALS:		1. Neat cement	2. Cement Grout	3. Bentonite	Other	bentonite hole plug		
	Grout Intervals:	From	4 ft.	to	24 ft.	From	ft.	to	ft.
	What is the nearest source of possible contamination:								
	1. Septic tank	4. Lateral lines	7. Pit privy	10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well			
	2. Sewer lines	5. Cess Pool	8. Sewage lagoon	11. Fuel storage	14. Abandon water well	16. Other (specify below)			
	3. Watertight sewer line	6. Seepage pit	9. Feed yard	12. Fertilizer storage					
Direction from well?		West			How many feet?		50 ft. plus		

[illegible]

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 4/4/2005 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 4/7/2005

under the business name of Harp Well & Pump Service Inc. by (signature) J o d d S. H a r p