


KSA 82a-1212

1 LOCATION OF WATER WELL: Sedgwick	FRACTION SW 1/4 SW 1/4 NW 1/4	SECTION NUMBER 33	TOWNSHIP NUMBER T 26 S	RANGE NUMBER R 1W E/W
Distance and direction from nearest town or city street address of well if located within city? 3407 Valeria Circle Wichita, Kansas				
2 WATER WELL OWNER: SCHNEIDEL, Darrel		Board of Agriculture, Division of Water Resource		
RR#, ST. ADDRESS, BOX #: 3407 Valeria Circle				
CITY, STATE: Wichita, Kansas		ZIP CODE:		Application Number:
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 67 ft.			
	ELEVATION:			
	Depth of groundwater Encountered:			
	WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 5/7/05			
Pump test data:		Well water was _____ ft. after _____ hours of pumping @ _____ gpm		
Est. Yield: _____ gpm		Well water was _____ ft. after _____ hours of pumping @ _____ gpm		
Bore Hole Diameter 12 in.		to 67 ft. and _____ in. to _____ ft.		
WELL WATER TO BE USED AS:				
1. Domestic 3. Feedlot 5. Public water supply <u>7. Lawn and garden only</u> 9. Dewatering 11. Injection well				
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below)				
Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted				
Was Water Well Disinfected? <u>YES</u> NO				
5 TYPE OF CASING USED:				
1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: <u>Glued</u> Threaded				
<u>2. PVC</u> 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26 Welded Clamped				
Blank casing diameter 5 in. to 47 ft., Dia. in. to ft., Dia. in. to ft.				
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214				
TYPE OF SCREEN OR PERFORATION MATERIAL:				
1. Steel 3. Stainless Steel 5. Fiberglass <u>7. PVC</u> 9. ABS 11. Other (specify)				
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE:				
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)				
2. Louvered shutter 4. Key punched 6. Wire wrapped <u>8. Saw cut</u> 10. Other (specify)				
SCREEN - PERFORATION INTERVAL From 47 ft. to 67 ft., From ft. to ft., From ft. to ft.				
GRAVEL PACK INTERVALS: From 24 ft. to 67 ft., From ft. to ft., From ft. to ft.				

6	GROUT MATERIALS:		1. Neat cement		2. Cement Grout		3. Bentonite		Other		bentonite hole plug		
	Grout Intervals:		From	4	ft.	to	24	ft.	From		ft.	to	ft.
	What is the nearest source of possible contamination:												
	1. Septic tank		4. Lateral lines		7. Pit privy		10. Livestock pens		13. Insecticide storage		15. Oil well/Gas well		
	2. Sewer lines		5. Cess Pool		8. Sewage lagoon		11. Fuel storage		14. Abandon water well		16. Other (specify below)		
	3. Watertight sewer line		6. Seepage pit		9. Feed yard		12. Fertilizer storage						
	Direction from well?		East						How many feet?		50 feet plus		

[illegible]

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. **reconstructed** or 3. **plugged** under my jurisdiction and was completed on (mo/day/year) **5/7/2005** and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. **236** This water well record was completed on (mo/day/year) **5-9-2005**

under the business name of **Harp Well & Pump Service Inc.** by (signature) *To dd S. Harp*